

# 2009 **FOURTRAX RINCON/GPScape**




*The power-packed  
Rincon—it's what  
happens when  
Honda pulls out  
all the stops.*

**FOURTRAX RINCON/GPScape** As Honda's most powerful utility ATV, you'd expect the Rincon® to have a great engine. And it does: a liquid-cooled, 700-class, single-cylinder, longitudinally-mounted engine specially tuned for low-rpm torque. This state-of-the-art powerplant is just as advanced as it is impressive, with electronic fuel-injection for instant, no-choke startups and precise throttle response, no matter how hot it is or how high you climb. For sure, agile traction we gave the Rincon our tough, yet precise, fully Independent Rear Suspension (IRS). And for power-when-you-need-it rideability, we added Honda's exclusive automotive-style three-speed automatic transmission and optional GPScape® navigation system.



Red



Olive



Blue



Natural Gear™ Camo

(FGA version available in Red and Natural Gear Camo only)

## UNIQUE FEATURES

- Liquid-cooled four-stroke features a single-cylinder, fuel-injected 675cc OHV engine.
- Automotive-style Honda automatic transmission features a hydraulic torque converter, three hydraulic clutches and an Electronic Control Unit (ECU).
- Fully independent rear suspension for comfortable riding over rough terrain.
- TraxLok® selectable 2WD/4WD system is push button actuated and lets you choose 2WD for lighter steering and 4WD to maximize traction.
- Optional GPScape-equipped version features oversized buttons that are easy to operate with gloves.

## SPECIFICATIONS

<b>Model</b>	<b>TRX680FA/TRX680FGA (with GPS)</b>
<b>ENGINE</b>	
Engine	675cc liquid-cooled OHV semi-dry-sump longitudinally mounted single-cylinder four-stroke
Bore & Stroke	102mm x 82.6mm
Induction	Electronic fuel injection (PGM-FI), 40mm throttle bodies
Ignition	Full-transistorized type with electronic advance
<b>CHASSIS / SUSPENSION / BRAKES</b>	
Front Suspension	Independent double-wishbone; 6.9-inch travel
Rear Suspension	Independent double-wishbone; 8.0-inch travel
Front Brake	Dual hydraulic 180mm disc
Rear Brake	Single hydraulic disc

<b>DIMENSIONS</b>	
Wheelbase	50.8 inches
Seat Height	34.5 inches
Ground Clearance	10.0 inches
Curb Weight*	648 pounds
	*Includes all standard equipment, required fluids and a full tank of fuel
Fuel Capacity	4.3 gallons, including 1.2-gallon reserve

<b>DRIVETRAIN</b>	
Transmission	Automatic with hydraulic torque converter, three forward gears, reverse and electronic controls

<b>FACTORY WARRANTY</b>	
1 Year	Coverage of defects in materials and workmanship

## ENVIRONMENTAL COMMITMENT

At Honda, we believe in performance and leadership, and that's why we're taking a leadership position when it comes to the environment. We continue to develop low-emission technologies for our current and future motorcycles, ATVs, scooters and personal watercraft. And that's the kind of performance everybody can appreciate.

UTILITY ATVs ONLY FOR RIDERS 16 & OLDER. ATVs CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, BE RESPONSIBLE. READ YOUR OWNER'S MANUAL. ALWAYS WEAR HELMET, EYE PROTECTION & PROTECTIVE CLOTHING. BE CAREFUL ON DIFFICULT TERRAIN. ALL ATV RIDERS SHOULD TAKE A TRAINING COURSE (FREE FOR NEW BUYERS, ASK YOUR DEALER OR CALL ASI 800-887-2887). NEVER RIDE: UNDER THE INFLUENCE OF DRUGS OR ALCOHOL, ON PAVED SURFACES, PUBLIC ROADS, WITH PASSENGERS, AT EXCESSIVE SPEEDS. NO STUNT RIDING. RESPECT THE ENVIRONMENT WHEN RIDING. Whenever you ride off-road, follow the "Tread Lightly!" guidelines, and always stay on established trails in approved areas. Operating your ATV with a modified engine, exhaust system, spark arrester or noise control system may be illegal. Natural Gear™ is a registered trademark of NATGEAR, LLC. FourTrax®, Rincon®, GPScape®, and TraxLok® are registered trademarks of Honda Motor Co., Ltd. ©2008 AHMC

