



2009 CRF230M SPECIFICATIONS

ENGINE

Engine Type	223cc air-cooled single-cylinder four-stroke
Bore and Stroke	65.5mm x 66.2mm
Induction	30mm CV carburetor
Ignition	CD
Compression Ratio	9.0:1
Value Train	SOHC; two-valve

DRIVE TRAIN

Transmission	Six-speed
Final Drive	#520 O-ring-sealed chain; 13T/38T

CHASSIS / SUSPENSION / BRAKES

Front Suspension	37mm leading-axle Showa® fork; 9.0 inches travel
Rear Suspension	Pro-Link® Showa single shock with adjustable spring-preload; 6.6 inches travel
Front Brake	Single 240mm disc
Rear Brake	220mm disc
Front Tire	110/70-17 Dunlop GT401 Arrowmax
Rear Tire	130/70-17 Dunlop GT401 Arrowmax

DIMENSIONS

Rake	23.9° (Caster Angle)
Trail	91mm (3.58 inches)
Wheelbase	52.6 inches
Seat Height	31.7 inches
Curb Weight	276 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	2.3 gallons, including 0.7-gallon reserve
Ground Clearance	9.3 inches

OTHER

Model ID	CRF230M
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.
Available Color	Black

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.
----------	--