



2009 FOURTRAX FOREMAN 4x4 SPECIFICATIONS

ENGINE

Engine Type	475cc air-cooled OHV longitudinally mounted single-cylinder four-stroke
Bore and Stroke	92mm x 71.5mm
Induction	36mm constant-velocity (CV) carburetor
Ignition	CD with electronic advance
Starter	Electric with auxiliary recoil
Compression Ratio	8.5:1

DRIVE TRAIN

Clutch	Automatic
Transmission	Five-speed with Reverse
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential

CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone; 6.7 inches travel
Rear Suspension	Swingarm with dual shocks; 6.7 inches travel
Front Brake	Dual hydraulic 180mm disc
Rear Brake	Sealed 180mm mechanical drum
Front Tire	25 x 8-12
Rear Tire	25 x 10-12

DIMENSIONS

Length	83 inches
Width	46.8 inches
Height	46.5 inches
Wheelbase	50.7 inches
Seat Height	33.9 inches
Ground Clearance	7.5 inches
Curb Weight	620 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	4.1 gallons, including 0.7-gallon reserve

OTHER

Model ID	TRX500FM
Emissions	Meets current California Air Resources Board (CARB) and EPA off-road emissions standards.
Available Colors	Black, NaturalGear™ Camouflage, Olive, Red
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.
----------	--