



2009 SILVER WING SPECIFICATIONS

ENGINE

Engine Type	582cc liquid-cooled four-stroke parallel-twin
Bore and Stroke	72mm x 71.5mm
Induction	Programmed Fuel Injection (PGM-FI) with automatic enricher circuit, four-hole injectors
Ignition	Computer-controlled fully transistorized with electronic advance
Compression Ratio	10.2:1
Valve Train	DOHC; four valves per cylinder

DRIVE TRAIN

Transmission	Automatic V-Matic belt drive
--------------	------------------------------

CHASSIS / SUSPENSION / BRAKES

Front Suspension	41mm hydraulic fork; 4.7 inches travel
Rear Suspension	Swingarm with dual hydraulic shocks with five-position spring-preload adjustability; 4.5 inches travel
Front Brake	Single 276mm disc with CBS three-piston caliper
Rear Brake	Single 240mm disc with CBS twin-piston caliper
Front Tire	120/80-14
Rear Tire	150/70-13

DIMENSIONS

Wheelbase	62.8 inches
Seat Height	29.7 inches
Curb Weight	540 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	4.2 gallons, including 0.9-gallon reserve

OTHER

Model ID	FSC600
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.
Available Color	Candy Dark Red

FACTORY WARRANTY INFORMATION

One Year	Transferable, unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.
----------	---