



2009 TRX250X SPECIFICATIONS

ENGINE

Engine Type	229cc air-cooled OHV longitudinally mounted single-cylinder four-stroke
Bore and Stroke	68.5mm x 62.2mm
Induction	22mm piston-valve carburetor
Ignition	CD with electronic advance
Starter	Electric

DRIVE TRAIN

Clutch	Honda SportClutch™
Transmission	Five-speed with Reverse
Driveline	Direct rear drive shaft

CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone; 5.9 inches travel
Rear Suspension	Swingarm with single shock; 5.7 inches travel
Front Brake	Dual hydraulic 174mm discs
Rear Brake	Sealed mechanical drum
Front Tire	22 x 7-10 knobby
Rear Tire	22 x 10-9 knobby

DIMENSIONS

Length	68.5 inches
Width	41.8 inches
Height	42.4 inches
Wheelbase	44.3 inches
Seat Height	31.4 inches
Ground Clearance	5.9 inches
Curb Weight	379 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	2.5 gallons, including 0.7-gallon reserve
Turning Radius	9.2 feet

OTHER

Model ID	TRX250X
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Colors	White, Red
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.
----------	------------------------------------------------------------------------------------------