



2009 TRX300X SPECIFICATIONS

ENGINE

Engine Type	282cc air-cooled SOHC single-cylinder four-stroke
Bore and Stroke	74mm x 65.5mm
Induction	32mm piston-valve with accelerator pump carburetor
Ignition	CD with electronic advance
Starter	Electric

DRIVE TRAIN

Clutch	Manual
Transmission	Five-speed with Reverse
Driveline	O-ring-sealed chain

CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone with dual hydraulic shocks; five-position spring-preload adjustability; 7.1 inches travel
Rear Suspension	Swingarm with single shock; five-position spring-preload adjustability; 7.9 inches travel
Front Brake	Dual hydraulic discs
Rear Brake	Single hydraulic disc
Front Tire	22 x 7-10 knobby
Rear Tire	22 x 10-9 knobby

DIMENSIONS

Length	67.7 inches
Width	43.5 inches
Height	41.8 inches
Wheelbase	45 inches
Seat Height	30.5 inches
Ground Clearance	4.6 inches
Curb Weight	388 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	2.2 gallons, including 0.5-gallon reserve
Turning Radius	10.2 feet

OTHER

Model ID	TRX300X
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Colors	White, Red
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.
----------	--