



2009 TRX400X SPECIFICATIONS

ENGINE

Engine Type	397cc RFVC™ air-cooled dry-sump single-cylinder four-stroke
Bore and Stroke	85mm x 70mm
Induction	38mm piston-valve with accelerator pump
Ignition	CD with electronic advance
Starter	Electric

DRIVE TRAIN

Clutch	Manual
Transmission	Five-speed with Reverse
Driveline	O-ring-sealed chain

CHASSIS / SUSPENSION / BRAKES

Front Suspension	Independent double-wishbone with Showa® shocks, five-position spring-preload adjustability; 8.2 inches travel
Rear Suspension	Pro-Link® fully adjustable single Showa shock; 9.1 inches travel
Front Brake	Dual hydraulic 174mm discs
Rear Brake	Single 220mm disc
Front Tire	22 x 7-10 knobby radial
Rear Tire	20 x 10-9 knobby

DIMENSIONS

Length	71.7 inches
Width	45.5 inches
Height	44 inches
Wheelbase	47.9 inches
Seat Height	32.8 inches
Ground Clearance	4.1 inches
Curb Weight	408 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	2.6 gallons (Including 0.4 gallon reserve)
Turning Radius	10.5 feet

OTHER

Model ID	TRX400X
Emissions	Meets current California Air Resources Board (CARB) off-road emissions standards.
Available Colors	Black (Limited 2009 color run, less than 500), Red/Black, Black/White
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.
----------	--