



2010 NT700V*

ENGINE

Engine Type	680cc liquid-cooled 52° V-twin
Bore and Stroke	81mm x 66mm
Induction	PGM-FI with automatic enrichment circuit, 40mm throttle bodies and 12-hole injectors
Ignition	Digital transistorized with electronic advance
Compression Ratio	10.0:1
Valve Train	SOHC; four valves per cylinder

DRIVE TRAIN

Transmission	Five-speed
Final Drive	Shaft

CHASSIS / SUSPENSION / BRAKES

Front Suspension	41mm telescopic fork; 4.5 inches travel
Rear Suspension	Single shock with spring-preload adjustability; 4.8 inches travel
Front Brake	Dual full-floating 296mm discs with CBS three-piston calipers
Rear Brake	Single 276mm disc with CBS three-piston caliper
Front Tire	120/70 ZR17 radial
Rear Tire	150/70 ZR17 radial

DIMENSIONS

Rake	28°50' (Caster Angle)
Trail	115mm (4.5 inches)
Wheelbase	58.1 inches
Seat Height	31.7 inches
Curb Weight	562 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	5.2 gallons, including 0.9-gallon reserve
Miles Per Gallon†	50 MPG

OTHER

Model ID	NT700VA
Available Color	Metallic Silver, Metallic Red
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.

FACTORY WARRANTY INFORMATION

One Year	Transferable, unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.
----------	---

†Honda's fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

*All figures are preliminary and subject to change.

©2009 American Honda Motor Co., Inc. - Motorcycle Division