



2013 SHADOW AERO SPECIFICATIONS*

ENGINE

Engine Type	745cc liquid-cooled 52° V-twin
Bore and Stroke	79mm x 76mm
Induction	PGM-FI with automatic enrichment circuit, one 34mm throttle body
Ignition	Digital transistorized with electronic advance
Compression Ratio	9.6:1
Valve Train	SOHC; three valves per cylinder

DRIVE TRAIN

Transmission	Wide-ratio five-speed
Final Drive	Shaft

CHASSIS / SUSPENSION / BRAKES

Front Suspension	41mm fork; 4.6 inches travel
Rear Suspension	Dual shocks with five-position spring-preload adjustability; 3.5 inches travel
Front Brake	Single 296mm disc with twin-piston caliper
Rear Brake	180mm drum
Front Tire	120/90-17
Rear Tire	160/80-15

DIMENSIONS

Rake (Caster Angle)	34.0°
Trail	161mm (6.3 inches)
Wheelbase	64.6 inches
Seat Height	25.9 inches
Curb Weight	560 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.7 gallons, including 0.9-gallon reserve
Estimated Fuel Economy†	56 MPG

OTHER

Model ID	VT750C
Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Black, Metallic Silver/Pearl White

FACTORY WARRANTY INFORMATION

One Year	Transferable, unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.
----------	---

*All figures are preliminary and subject to change.

† Honda's fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

©2012 American Honda Motor Co., Inc. — Motorcycle Division