



2014 FURY SPECIFICATIONS*

ENGINE

Engine Type	1312cc liquid-cooled 52° V-twin
Bore and Stroke	89.5mm x 104.3mm
Induction	PGM-FI with automatic enrichment circuit, one 38mm throttle body
Ignition	Digital with 3-D mapping, two spark plugs per cylinder
Compression Ratio	9.2:1
Valve Train	SOHC; three valves per cylinder

DRIVE TRAIN

Transmission	Five-speed
Final Drive	Shaft

DRIVE TRAIN CHASSIS / SUSPENSION / BRAKES

Front Suspension	45mm fork; 4.0 inches travel
Rear Suspension	Single shock with adjustable rebound-damping and five-position spring-preload adjustability 3.7 inches travel
Front Brake	Single 336 mm disc with twin-piston caliper
Rear Brake	Single 296 mm disc with single-piston caliper
Front Tire	90/90-21
Rear Tire	200/50-18

DIMENSIONS

Rake (Caster Angle)	32.0°
Trail	92mm (3.6 inches)
Wheelbase	71.2 inches
Seat Height	26.9 inches
Curb Weight	666 pounds (Includes all standard equipment, required fluids and full tank of fuel—ready to ride.)
Fuel Capacity	3.4 gallons
Estimated Fuel Economy†	45 mpg

OTHER

Model ID	VT1300CX
Emissions	Meets current EPA standards. California version meets current California Air Resources) standards Board (CARB) standards and may differ slightly due to emissions equipment.
Available Colors	Black, Matte Pearl White/Red

FACTORY WARRANTY INFORMATION

One Year	Unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.
----------	---

*All figures are preliminary and subject to change.

Miles per gallon values are calculated estimates of fuel consumed during laboratory exhaust emissions tests specified by the EPA, not during on road riding. Use for comparison purposes only. Your actual mileage will vary depending on how you ride and maintain your vehicle, weather, road conditions, tire pressure, cargo and accessories, rider and passenger weight, and other factors.

©2014 American Honda Motor Co., Inc. — Motorcycle Division