



2017 MONTESA COTA 300RR SPECIFICATIONS*

ENGINE

Engine Type	288cc liquid-cooled single-cylinder four-stroke
Bore and Stroke	80.0mm x 57.2mm
Induction	Programmed Fuel Injection (PGM-FI) 28mm throttle body
Ignition	Electronically controlled digital transistorized
Compression Ratio	10.5:1
Valve Train	Unicam®, 4 valves

DRIVE TRAIN

Transmission	Close-ratio 5-speed transmission
Final Drive	#520 Chain, 10T/41T

SUSPENSION / BRAKES / WHEELS

Front Suspension	39mm Tech telescopic fork with aluminum tubes; preload, compression damping and rebound damping adjustment, 6.6 inch stroke
Rear Suspension	Pro-Link® system with Showa® shock; preload rebound damping adjustment; 6.7 inch stroke
Front Brake	Single 185mm hydraulic disc with 4-piston caliper and sintered metal pads
Rear Brake	Single 150mm hydraulic disc with 2-piston caliper and sintered metal pads
Front Tire	80/100-21 Michelin
Rear Tire	120/100-R18 Michelin

DIMENSIONS

Rake(Caster Angle)	23.0°
Wheelbase	52.0 inches
Trail	63mm (2.48 inches)
Seat Height	25.6 inches
Curb Weight**	162 pounds
Fuel Capacity	0.5 gallons
Ground Clearance	13.2 inches

OTHER

Model ID	MRT300H
Available Colors	Red

*All figures are preliminary and subject to change. **Includes all standard equipment, required fluids and full tank of fuel—ready to ride. Meets current CARB and EPA off-road emissions standards.

©2016 American Honda Motor Co., Inc. - Motorcycle Division