





ENGINE	
Engine Type	259cc liquid-cooled single-cylinder four-stroke
Bore and Stroke	78.0mm x 54.2mm
Induction	Programmed Fuel Injection (PGM-FI) 28mm throttle body
Ignition	Electronically controlled digital transistorized
Compression Ratio	10.5:1
Valve Train	Unicam®, 4 valves

DRIVE TRAIN	
Transmission	Close-ratio five-speed transmission
Final Drive	#520 chain; 10T/41T

SUSPENSION / BRAKES / WHEELS		
Front Suspension	39mm TECH cartridge-type telescopic fork with Pre-load extension adjustments; 6.9 inch stroke	
Rear Suspension	Pro-Link® system, R16V single shock absorber with preload extension adjustment; 6.7 inch stroke	
Front Brake	Single 185mm hydraulic disc with 4-piston caliper and sintered metal pads	
Rear Brake	Single 150mm hydraulic disc with 2-piston caliper and sintered metal pads	
Front Tire	2.75-21 Dunlop	
Rear Tire	4.00-18 Dunlop	

DIMENSIONS	
Wheelbase	52.0 inches
Rake (Caster Angle)	23.0°
Trail	63mm (2.48 inches)
Seat Height	25.6 inches
Curb Weight**	163.7 pounds
Fuel Capacity	0.5 gallons
Ground Clearance	13.2 inches
OTHER	
Model ID	MRT260H
Available Colors	White/Blue/Red