



## READY FOR EVEN BIGGER ADVENTURES

There's big news when it comes to our awesome Africa Twin this year: More features. More torque. More refinement. And a major change in our Adventure Sports models that riders are going to love. In terms of the engine, bumping up the compression ratio and changing the valve timing means a seven-percent torque boost — especially in the bottom end and midrange — with no loss of peak power. A new cowl and windshield enhance weather protection. New tubeless tires front and rear. And the biggest news of all — our Adventure Sports model now features a 19-inch front wheel and new suspension that lowers the bike's center of gravity and enhances on-road riding.

For 2024 we're offering four different Africa Twin models. Our standard Africa Twin is a great choice for serious off-road enthusiasts, with either a six-speed manual transmission or our optional automatic DCT. For long-distance adventure touring, check out our two Africa Twin Adventure Sports ES models: They offer special features like electronically controlled suspension, an adjustable windscreen, larger fuel tank, heated grips, a 19-inch front wheel, and more. They too are available with either a manual transmission or automatic DCT. And every Africa Twin features cruise control and supports Apple CarPlay™ and Android Auto. When it comes to an adventure touring motorcycle, if you can dream it, an Africa Twin will take you there.

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. RESPECT THE ENVIRONMENT WHEN RIDING. Africa Twin® is a registered trademark of Honda Motor Co., Ltd. Pro-Link® is a registered trademark of Showa Mtg., Inc. Apple CarPlay and iPhone are trademarks of Apple Inc. For using Apple CarPlay, connection to a commercially available Bluetooth headset is necessary. See owner's manual for Bluetooth headset requirements. Unicam® and Pro-Link® are registered trademarks of Honda Motor Co ©2024 American Honda Motor Co., Inc



Accessorized European Models shown



# 2024 Africa Twin Adventure Sports ES





**Africa Twin/DCT**



  
GRAND PRIX RED

**Africa Twin  
Adventure Sports ES/DCT**



  
PEARL WHITE

## FEATURES & BENEFITS

### 1084cc TWIN-CYLINDER ENGINE

The CRF1100L Africa Twin sports one of the best engines ever in an adventure bike. The parallel-twin design is narrow, and delivers torque everywhere from idle to redline. You'll have more grunt down low, and cruise easy on the open road.

### CRUISE CONTROL

Here's one of the worst-kept secrets in the motorcycling world — Honda's Africa Twins make great long-distance touring bikes. To that end, we've equipped our Africa Twin models with cruise control, just like our Gold Wings. Your next adventure really starts a couple of hundred miles away? No problem!

### LONG-TRAVEL FRONT SUSPENSION

The inverted Showa fork is fully adjustable with huge 45mm tubes and 9.1 inches of travel — the most front-end travel in the 1000cc off-road class. Our Adventure Sports models get 210mm (8.3 inches) of front travel to match the 19-inch front-wheel fitment.

### Apple CarPlay™ AND ANDROID AUTO™

Apple CarPlay™\* seamlessly integrates your compatible iPhone®\* into your new Africa Twin, and Android Auto™ does the same for your Android phone. That means you can use your devices to access maps, music, and other services easily. Available Bluetooth®\*\* -enabled wireless headsets let you communicate more easily than ever.







# 2024 Africa Twin Africa Twin Adventure Sports ES



Africa Twin



Africa Twin Automatic DCT

|                          | Africa Twin  | Africa Twin Automatic DCT  |
|--------------------------|--|--|
| <b>ENGINE TYPE</b>       | 1083cc liquid-cooled Unicam® four-stroke 22.5° parallel-twin                   | 1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin                    |
| <b>BORE AND STROKE</b>   | 92.0mm x 81.5mm  | 92.0mm x 81.5mm  |
| <b>INDUCTION</b>         | PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body        | PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body        |
| <b>VALVE TRAIN</b>       | Unicam SOHC; four valves per cylinder  | Unicam SOHC; four valves per cylinder  |
| <b>COMPRESSION RATIO</b> | 10.5:1   | 10.5:1   |
| <b>TRANSMISSION</b>      | 6-speed manual   | 6-speed Automatic DCT  |
| <b>FINAL DRIVE</b>       | #525 Chain; 16T/42T  | #525 Chain; 16T/42T  |
| <b>FRONT SUSPENSION</b>  | 45mm inverted telescopic fork; 9.0 inches of travel                            | 45mm inverted telescopic fork; 9.0 inches of travel                            |
| <b>REAR SUSPENSION</b>   | Pro-Link® system w/ single shock; 8.7 inches of travel                         | Pro-Link system w/ single shock; 8.7 inches of travel                          |
| <b>FRONT BRAKES</b>      | Dual 310mm discs with four-piston calipers; ABS                                | Dual 310mm discs with four-piston calipers; ABS                                |
| <b>REAR BRAKES</b>       | Single 256mm disc with single-piston caliper; ABS                              | Single 256mm disc with single-piston caliper; ABS                              |
| <b>FRONT TIRES</b>       | 90/90-21   | 90/90-21   |
| <b>REAR TIRES</b>        | 150/70R-18   | 150/70R-18   |
| <b>RAKE</b>              | 27°  | 27°  |
| <b>TRAIL</b>             | 4.5 inches   | 4.5 inches   |
| <b>WHEELBASE</b>         | 62.0 inches  | 62.0 inches  |
| <b>SEAT HEIGHT</b>       | Standard position 34.3 inches/Low position 33.5 inches                         | Standard position 34.3 inches/Low position 33.5 inches                         |
| <b>CURB WEIGHT</b>       | 510 lbs—Includes all standard equipment, required fluids and full tank of fuel | 535 lbs—Includes all standard equipment, required fluids and full tank of fuel |
| <b>FUEL CAPACITY</b>     | 5.0 gallons including 1.0-gallon reserve                                       | 5.0 gallons including 1.0-gallon reserve                                       |





# 2024 Africa Twin Africa Twin Adventure Sports ES



**Africa Twin Adventure Sports ES**



**Africa Twin Adventure Sports ES DCT**

|                          |   |   |
|--------------------------|---|---|
| <b>ENGINE TYPE</b>       | 1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin                       | 1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin                       |
| <b>BORE AND STROKE</b>   | 92.0mm x 81.5mm   | 92.0mm x 81.5mm   |
| <b>INDUCTION</b>         | PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body           | PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body           |
| <b>VALVE TRAIN</b>       | Unicam SOHC; four valves per cylinder   | Unicam SOHC; four valves per cylinder   |
| <b>COMPRESSION RATIO</b> | 10.5:1  | 10.5:1  |
| <b>TRANSMISSION</b>      | 6-speed manual  | 6-speed Automatic DCT   |
| <b>FINAL DRIVE</b>       | #525 Chain; 16T/42T   | #525 Chain; 16T/42T   |
| <b>FRONT SUSPENSION</b>  | 45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel    | 45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel    |
| <b>REAR SUSPENSION</b>   | Pro-Link single shock with fork with electronic adjustment ; 7.9 inches of travel | Pro-Link single shock with fork with electronic adjustment ; 7.9 inches of travel |
| <b>FRONT BRAKES</b>      | Dual 310mm discs with four-piston calipers; ABS                                   | Dual 310mm discs with four-piston calipers; ABS                                   |
| <b>REAR BRAKES</b>       | Single 256mm disc with single-piston caliper; ABS                                 | Single 256mm disc with single-piston caliper; ABS                                 |
| <b>FRONT TIRES</b>       | 110/80-19   | 110/80-19   |
| <b>REAR TIRES</b>        | 150/70R-18  | 150/70R-18  |
| <b>RAKE</b>              | 27°   | 27°   |
| <b>TRAIL</b>             | 4.2 inches  | 4.2 inches  |
| <b>WHEELBASE</b>         | 61.8 inches   | 61.8 inches   |
| <b>SEAT HEIGHT</b>       | Standard position 33.7 inches/Low position 32.9 inches                            | Standard position 33.7 inches/Low position 32.9 inches                            |
| <b>CURB WEIGHT</b>       | 535 lbs—Includes all standard equipment, required fluids and full tank of fuel    | 559 lbs—Includes all standard equipment, required fluids and full tank of fuel    |
| <b>CURB WEIGHT</b>       | 6.6 gallons including 1.0-gallon reserve  | 6.6 gallons including 1.0-gallon reserve  |