



ADventure BEYOND LIMITS

Adventure calls in two options: the Africa Twin and Africa Twin Adventure Sports ES. Both pack a powerful 1083cc engine and long-distance comfort, plus optional DCT. The standard model journeys off-road with its 21-inch front tire, while the Adventure Sports ES goes the road route with electronic suspension and a 19-inch front wheel. Your journey starts here!



2025 Africa Twin Adventure Sports ES

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. RESPECT THE ENVIRONMENT WHEN RIDING. Africa Twin® is a registered trademark of Honda Motor Co., Ltd. Pro-Link® is a registered trademark of Showa Mfg., Inc. Apple CarPlay and iPhone are trademarks of Apple Inc. For using Apple CarPlay, connection to a commercially available Bluetooth headset is necessary. See owner's manual for Bluetooth headset requirements. Unicam® and Pro-Link® are registered trademarks of Honda Motor Co. ©2024 American Honda Motor Co., Inc



Africa Twin/DCT




MATTE BLACK METALLIC

**Africa Twin
Adventure Sports ES/DCT**




PEARL WHITE

FEATURES & BENEFITS

1083cc TWIN-CYLINDER ENGINE

A narrow 1083cc parallel-twin engine delivers torque smoothly throughout the RPM range, making them great for everything from off-road riding to highway cruising.

CRUISE CONTROL

All Africa Twin models come factory-equipped with cruise control for touring, and you'll thank us after those high-mileage rides.

LOW CENTER OF GRAVITY

By placing heavy components like the battery near the bike's center of gravity and using a compact engine, we've created a platform for excellent handling.

TFT TOUCHSCREEN DISPLAY

A 6.5-inch LCD instrument touch panel features three displays and can show a multitude of information, depending on your needs.





2024 Africa Twin Africa Twin Adventure Sports ES



Africa Twin



Africa Twin Automatic DCT

ENGINE TYPE	1083cc liquid-cooled Unicam® four-stroke 22.5° parallel-twin	1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin
BORE AND STROKE	92.0mm x 81.5mm	92.0mm x 81.5mm
INDUCTION	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10.5:1	10.5:1
TRANSMISSION	6-speed manual	6-speed Automatic DCT
FINAL DRIVE	#525 Chain; 16T/42T	#525 Chain; 16T/42T
FRONT SUSPENSION	45mm inverted telescopic fork; 9.0 inches of travel	45mm inverted telescopic fork; 9.0 inches of travel
REAR SUSPENSION	Pro-Link® system w/ single shock; 8.7 inches of travel	Pro-Link system w/ single shock; 8.7 inches of travel
FRONT BRAKES	Dual 310mm discs with four-piston calipers; ABS	Dual 310mm discs with four-piston calipers; ABS
REAR BRAKES	Single 256mm disc with single-piston caliper; ABS	Single 256mm disc with single-piston caliper; ABS
FRONT TIRES	90/90-21	90/90-21
REAR TIRES	150/70R-18	150/70R-18
RAKE	27°	27°
TRAIL	4.5 inches	4.5 inches
WHEELBASE	62.0 inches	62.0 inches
SEAT HEIGHT	Standard position 34.3 inches/Low position 33.5 inches	Standard position 34.3 inches/Low position 33.5 inches
CURB WEIGHT	510 lbs—Includes all standard equipment, required fluids and full tank of fuel	535 lbs—Includes all standard equipment, required fluids and full tank of fuel
FUEL CAPACITY	5.0 gallons including 1.0-gallon reserve	5.0 gallons including 1.0-gallon reserve



2024 Africa Twin Africa Twin Adventure Sports ES



Africa Twin Adventure Sports ES



Africa Twin Adventure Sports ES DCT

ENGINE TYPE	1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin	1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin
BORE AND STROKE	92.0mm x 81.5mm	92.0mm x 81.5mm
INDUCTION	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10.5:1	10.5:1
TRANSMISSION	6-speed manual	6-speed Automatic DCT
FINAL DRIVE	#525 Chain; 16T/42T	#525 Chain; 16T/42T
FRONT SUSPENSION	45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel	45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel
REAR SUSPENSION	Pro-Link single shock with fork with electronic adjustment ; 7.9 inches of travel	Pro-Link single shock with fork with electronic adjustment ; 7.9 inches of travel
FRONT BRAKES	Dual 310mm discs with four-piston calipers; ABS	Dual 310mm discs with four-piston calipers; ABS
REAR BRAKES	Single 256mm disc with single-piston caliper; ABS	Single 256mm disc with single-piston caliper; ABS
FRONT TIRES	110/80-19	110/80-19
REAR TIRES	150/70R-18	150/70R-18
RAKE	27°	27°
TRAIL	4.2 inches	4.2 inches
WHEELBASE	61.8 inches	61.8 inches
SEAT HEIGHT	Standard position 33.7 inches/Low position 32.9 inches	Standard position 33.7 inches/Low position 32.9 inches
CURB WEIGHT	535 lbs—Includes all standard equipment, required fluids and full tank of fuel	559 lbs—Includes all standard equipment, required fluids and full tank of fuel
CURB WEIGHT	6.6 gallons including 1.0-gallon reserve	6.6 gallons including 1.0-gallon reserve