



CBR600RR/ABS



PERFORMANCE AT ITS BEST

Sportbikes—especially 600-class machines—are for riders who want to feel the highest degree of connection with their motorcycles. Because the greater the connection, the more rewarding the ride. And that's why we strive to make our CBR®600RR and CBR600RR ABS as good as they are. The high-revving inline-four engine is instantly responsive. The aluminum chassis and premium suspension precisely connect you with the road like nothing else. And only a 600 can give you the light, crisp handling so many sportbike riders find so attractive. Available with optional anti-lock brakes, the CBR600RR is the best example of a highly refined breed. Is it for you? Ride one and see.



ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. CBR®, Pro-Link® and HMAS™ are trademarks of Honda Motor Co., Ltd. ©2021 American Honda Motor Co., Inc.



2022 CBR600RR/ABS





GRAND PRIX RED TRI COLOR

SPECIFICATIONS

ENGINE TYPE 599cc liquid cooled in-line four cylinder

BORE AND STROKE 67mm x 42.5mm

COMPRESSION RATIO 12.2:1

VALVE TRAIN DOHC: four valves per cylinder

INDUCTION Dual Stage Fuel Injection (DSFI) with 40mm throttle bodies, Denso

12-hole injectors

Computer-controlled digital transistorized with 3-D mapping IGNITION

TRANSMISSION Close-ratio six-speed

FINAL DRIVE #525 O-ring chain; 16T/42T

FRONT SUSPENSION 41mm inverted Big Piston Fork with spring preload, rebound and compression damping adjustability; 4.3 inches travel

REAR SUSPENSION Unit Pro-Link® HMAS™ single shock with spring preload, rebound and

compression damping adjustability; 5.1 inches travel

FRONT BRAKE Dual radial-mounted four-piston calipers with full-floating 310mm discs/ Honda Combined ABS

REAR BRAKE Single-caliper 220mm disc/Honda Combined ABS

FRONT TIRE 120/70ZR-17 radial **REAR TIRE** 180/55ZR-17 radial

WHEELBASE 53.9 inches TRAIL 3.9 inches 32.3 inches **SEAT HEIGHT**

RAKE (CASTER ANGLE) 23.5°

FUEL CAPACITY 4.8 gallons

CURB WEIGHT 410 pounds/ABS 434 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)

FEATURES & BENEFITS



RADIAL-MOUNTED FRONT-BRAKE CALIPERS

The CBR600RR uses radial-mounted monoblock front-brake calipers. This construction makes the caliper stiffer, and that means you get better brake feel for more linear, powerful stopping. Each caliper also uses four chromium-plated aluminum pistons for smooth, friction-free operation.



CENTRALLY LOCATED FUEL TANK

The CBR600RR's 4.8-gallon fuel tank is positioned in the center of the chassis and low in the frame. This allows for a more compact design, but even more important helps centralize the bike's mass. Increased mass centralization means the CBR is more responsive to rider input, especially when leaning the bike into a turn or standing it up at the exit.



Honda ELECTRONIC STEERING DAMPER (HESD)

Most steering dampers only sense handlebardeflection speed. The Honda Electronic Steering Damper (HESD) is way more sophisticated. It also detects vehicle speed, and adjusts damping proportionally. That helps maintain low-speed maneuverability while providing excellent, predictable high-speed handling.



DUAL-STAGE FUEL INJECTION

Two sets of injectors per cylinder ensure both low and high-rpm performance. You get nearinstantaneous high-rpm response, along with great low-rpm metering and clean running.