



TWO SIZES. ONE LEGENDARY RIDE.

With user-friendly power, legendary Honda reliability, and big bike-style manual clutch, the CRF125F is ready for riders on the rise. Available in both standard and Big Wheel trims, it features fuel injection, electric start, and a durable four-stroke engine — perfect for stepping up or anyone ready to hit the trail and never look back.

CRF/Fs ARE INTENDED FOR OFF-ROAD OPERATION ONLY. PARENTS NEED TO CONSIDER A RIDER'S AGE, SIZE, ABILITY AND MATURITY BEFORE ALLOWING THEM TO RIDE. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING, AND PLEASE RESPECT THE ENVIRONMENT. OBEY THE LAW AND READ THE OWNER'S MANUAL THOROUGHLY. Always stay on established trails in approved riding areas. CRF® and Pro-Link® are registered trademarks of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.



2026 CRF125F/ CRF125FB





CRF125F



CRF125FB Big Wheel



FEATURES & BENEFITS

RELIABLE ENGINE

The four-stroke, single-cylinder engine has a broad powerband and offers dependable performance for beginners. Fuel injection enhances its efficiency.

PROVEN MANUAL CLUTCH

The heavy-duty traditional manual clutch is durable and helps promote smooth shifting.

STEEL FRAME AND SWINGARM

We designed these bikes with strong, twin-spar-type steel frames and swingarms that can handle the bumps and dings of off-road riding.

BIG-WHEEL VERSION AVAILABLE

Looking for something a little larger? Check out our Big Wheel trim — the same great bike but a better fit for taller riders with its larger wheels and higher seat height.





2026 CRF125F/ CRF125FB



CRF125F

CRF125FB

	CRF125F	CRF125FB
ENGINE TYPE	125cc air-cooled single-cylinder four-stroke	125cc air-cooled single-cylinder four-stroke
BORE AND STROKE	52.4mm x 57.9mm	52.4mm x 57.9mm
INDUCTION	Fuel-injection; 22mm throttle bore	Fuel-injection; 22mm throttle bore
VALVE TRAIN	SOHC; two valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	9.0:1	9.0:1
FINAL DRIVE	13T/46T	13T/46T
TRANSMISSION	Four-speed	Four-speed
FRONT SUSPENSION	31mm leading-axle fork; 5.9-inches of travel	31mm leading-axle fork; 6.7-inches of travel
REAR SUSPENSION	Pro-Link® single-shock; 5.5-inches of travel	Pro-Link single-shock; 6.6-inches of travel
FRONT BRAKE	Single 220mm disc	Single 220mm disc
REAR BRAKE	95mm single-leading-shoe drum	95mm single-leading-shoe drum
FRONT TIRE	70/100-17	70/100-19
REAR TIRE	90/100-14	90/100-16
RAKE	27.5°	27.5°
TRAIL	3.2 inches	3.7 inches
WHEELBASE	48.0 inches	49.4 inches
SEAT HEIGHT	29.1 inches	30.9 inches
GROUND CLEARANCE	8.3 inches	10.3 inches
CURB WEIGHT	194 pounds (Includes all standard equipment, required fluids and a full tank of fuel)	199 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	1.0 gallon	1.0 gallon