



## CHOICE OF CHAMPIONS

Motorcycle racing is one of the most demanding sports in the world, and when the gate drops you better be totally dialed in — your fitness, your skills, and your equipment. And that's why the best riders in the world roll up to the start line on a Honda CRF®450R. Look at Team Honda HRC's Chase Sexton, who clinched the 2023 AMA Supercross championship. Or Jett Lawrence on his CRF®450R in the motocross nationals. When Honda introduced the first CR250M Elsinore fifty years ago, we changed motocross forever. For 2024, our CRF450R continues the legacy of winning, combining handling, power, suspension and refinement like nothing else on the track. And if you're looking for the absolute best of the best, check out our CRF450RWE Works Edition. It adds special touches like an exclusive Yoshimura exhaust, Twin Air filter, Throttle Jockey seat cover, Hinson clutch basket and cover, premium DID DirtStar LT-X rims, Kashima and titanium oxide-coated fork, a red cylinder head cover, and hands-on touches like special cylinder-head porting.



# 2024 CRF450R/ Works Edition

CRF450X IS INTENDED FOR OFF-ROAD OPERATION ONLY. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING, AND PLEASE RESPECT THE ENVIRONMENT. OBEY THE LAW AND READ THE OWNER'S MANUAL THOROUGHLY. ALWAYS STAY ON ESTABLISHED TRAILS IN APPROVED RIDING AREAS. Showa® is a registered trademark of Showa Mfg., Inc. CRF®, Unicam® and Pro-Link® are registered trademarks of Honda Motor Co., Ltd. ©2023 American Honda Motor Co., Inc.



Professional Rider Shown on closed course

## CRF450R



## CRF450R Works Edition



## FEATURES & BENEFITS

### LIGHT NARROW FRAME – HANDLING

By making the frame's main spars narrow, we save weight, but more important we make the chassis more responsive by fine-tuning the lateral rigidity. The result is a bike that gets into, around, and out of corners faster.

### HYDRAULIC CLUTCH

The CRF450R features the first hydraulically actuated dirtbike clutch we've offered outside of our works bikes. You get a clutch-lever pull that's ten percent lighter at its peak, even though it's paired with a strong, eight-plate clutch.

### SEALED AIRBOX AND FILTER

Along with the special air filter, the airbox shape helps deliver more torque. And because the CRF450R's filter has no rubber gasket where it interfaces with the intake boot, cleaning and servicing the filter is faster and less messy than ever.

### EXCLUSIVE WORKS EDITION

The CRF450RWE Works Edition includes a hand-ported cylinder head; Hinson clutch basket and cover; Throttle Jockey seat cover; upgraded DID DirtStar LT-X rims; an exclusive Yoshimura exhaust system; revalved suspension; and much more.







# 2024 CRF450R/ Works Edition



CRF450R



CRF450R Works Edition

<b>ENGINE TYPE</b>	450cc liquid-cooled single cylinder	450cc liquid-cooled single cylinder
<b>BORE AND STROKE</b>	96.0mm x 62.1mm	96.0mm x 62.1mm
<b>INDUCTION</b>	Programmed Fuel Injection (PGM-FI); 44mm downdraft throttle body	Programmed Fuel Injection (PGM-FI); 44mm downdraft throttle body
<b>VALVE TRAIN</b>	Unicam® SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
<b>COMPRESSION RATIO</b>	13.5:1	13.5:1
<b>FINAL DRIVE</b>	#520 Chain; 13T/49T	#520 Chain; 13T/49T
<b>TRANSMISSION</b>	Close-ratio five-speed	Close-ratio five-speed
<b>FRONT SUSPENSION</b>	49mm inverted Showa® fork with 13-position rebound and 15-position compression-damping adjustability; 12.2-inch travel	49mm inverted Showa fork with 13-position rebound and 15-position compression-damping adjustability; 12.2-inch travel
<b>REAR SUSPENSION</b>	Pro-Link® Showa single shock with adjustable spring preload, 11-position rebound and six-position high- and low-speed compression-damping adjustability; 12.4-inch travel	Pro-Link Showa single shock with adjustable spring preload, 11-position rebound and six-position high- and low-speed compression-damping adjustability; 12.4-inch travel
<b>FRONT BRAKES</b>	Single 260mm disc with twin-piston caliper	Single 260mm disc with twin-piston caliper
<b>REAR BRAKES</b>	Single 240mm disc	Single 240mm disc
<b>FRONT TIRES</b>	Dunlop MX33; 80/100-21	Dunlop MX33; 80/100-21
<b>REAR TIRES</b>	Dunlop MX33; 120/80-19	Dunlop MX33; 120/80-19
<b>RAKE</b>	27.1°	27.1°
<b>TRAIL</b>	4.5 inches	4.5 inches
<b>WHEELBASE</b>	58.3 inches	58.3 inches
<b>SEAT HEIGHT</b>	38.0 inches	38.0 inches
<b>GROUND CLEARANCE</b>	13.2 inches	13.2 inches
<b>CURB WEIGHT</b>	245 pounds (Includes all standard equipment, required fluids and a full tank of fuel)	245 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
<b>FUEL CAPACITY</b>	1.7 gallons	1.7 gallons