

WORKS HARD. RIDES SMOOTH.

Some jobs—and some trails—are tough enough as they are, and you don't need to be riding an ATV that adds to the workload. Which is precisely why we build our Honda FourTrax Foreman® Rubicon®. It's a tough-as-nails ATV with a plush, comfortable ride, thanks to its Independent Rear Suspension (IRS). Plus, we give every Rubicon a single-cylinder 518cc engine, tough front and rear racks, an easy-to-use reverse system, sharp styling, a handy utility box, and more. With four models, it's easy to choose the right mix of features, like our automatic DCT or a manual transmission and power steering that's right for you. And every Rubicon offers our famous Honda durability, reliability, and overall quality—a winning combination that sets them apart. Make sure you check out our new Black Forest Green model this year too!

UTILITY ATVS ARE RECOMMENDED FOR RIDERS 16 YEARS AND OLDER, ATVS CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, BE RESPONSIBLE. READ THE OWNER'S MANUAL. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. BE CAREFUL ON DIFFICULT TERRAIN. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, ON PAYED SURFACES, ON PUBLIC ROADS, WITH PASSENGERS, OR AT EXCESSIVE SPEEDS. NO STUNT RIDING. RESPECT THE ENVIRONMENT WHEN RIDING. FourTrax®, Rubicon®, Phantom Camo® and Honda Pro-Connect® and TraxLok® are registered trademarks of Honda Motor Co., Ltd. ©2022 American Honda Motor Co., Inc.



2023 FourTrax Foreman Rubicon 4x4





FourTrax Foreman Rubicon 4x4 EPS





FourTrax Foreman Rubicon 4x4 Automatic DCT



FourTrax Foreman Rubicon 4x4
Automatic DCT EPS





FourTrax Foreman Rubicon 4x4
Automatic DCT EPS Deluxe





FEATURES & BENEFITS

POWERFUL 518cc ENGINE

Every Foreman Rubicon model features a tough 518cc engine with the horsepower and torque you need for great performance. This power also gives it better hill-climbing ability. Bottom line: Work or play, this is one ATV that always delivers!

ELECTRIC REVERSE

Available on our Automatic DCT models, this single lever is convenient and easy to operate. It's especially useful when you have to shift from forward to reverse repeatedly, like when you're plowing snow.

FRONT/ REAR CARGO RACKS

The Rubicon's racks feature strong steel construction and a large flat area. Better still, they're designed so it's easy to attach and remove cargo boxes and other accessories in our Honda Pro-Connect™ line, adding to your Rubicon's versatility.

INDEPENDENT REAR SUSPENSION (IRS)

The Rubicon's Independent Rear Suspension (IRS) returns two big benefits: First, it helps ensure constant tire contact with the ground for superior traction; second, it gives you a smooth ride over rough terrain, so you don't get beat up on the trail.





	Four Irax Foreman Rubicon 4x4 EPS	Four trax Foreman Rubicon 4x4 Automatic DCT
ENGINE TYPE	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke
BORE AND STROKE	96.0mm x 71.5mm	96.0mm x 71.5mm
INDUCTION	PGM-FI; 36mm throttle body	PGM-FI; 36mm throttle body
STARTER	Electric with optional auxiliary recoil	Electric with optional auxiliary recoil
VALVE TRAIN	OHV; two valves per cylinder	OHV; two valves per cylinder
COMPRESSION RATIO	9.5:1	9.5:1
CLUTCH	Automatic	Automatic
TRANSMISSION	Five-speed manual with reverse	Five-speed automatic dual-clutch transmission with reverse and Low/Drive subtransmission
DRIVELINE	Direct front and rear driveshafts with TraxLok®; locking front differential	Direct front and rear driveshafts with TraxLok®; locking front differential
FRONT SUSPENSION	Independent double-wishbone; 7.3-inch travel	Independent double-wishbone; 7.3-inch travel
REAR SUSPENSION	Independent dual-arm; 8.5-inch travel	Independent dual-arm; 8.5-inch travel
FRONT BRAKES	Dual 190mm discs	Dual 190mm discs
REAR BRAKES	Dual 170mm discs	Dual 170mm discs
FRONT TIRES	25 x 8-12	25 x 8-12
REAR TIRES	25 x 10-12	25 x 10-12
LENGTH	86.0 inches	86.0 inches
WIDTH	47.4 inches	47.4 inches
HEIGHT	48.7 inches	48.7 inches
WHEELBASE	50.9 inches	50.9 inches
SEAT HEIGHT	36.4 inches	36.3 inches
TOWING CAPACITY	1322 pounds	1322 pounds
GROUND CLEARANCE	9.8 inches	9.7 inches
CURB WEIGHT	697 pounds (includes all standard equipment, required fluids and a full tank of fuel)	710 pounds (includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	3.9 gallons, including 1.3-gallon reserve	3.9 gallons, including 1.3-gallon reserve
FRONT RACK CAPACITY	99 pounds	99 pounds
REAR RACK CAPACITY	187 pounds	187 pounds



	Tour nax Foreman Habiton 1x Frateinate Bot Er o	Toda max i oroman masicon ix i y atomatic so i si o solaxe
ENGINE TYPE	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke
BORE AND STROKE	96.0mm x 71.5mm	96.0mm x 71.5mm
INDUCTION	PGM-FI; 36mm throttle body	PGM-FI; 36mm throttle body
STARTER	Electric with optional auxiliary recoil	Electric with optional auxiliary recoil
VALVE TRAIN	OHV; two valves per cylinder	OHV; two valves per cylinder
COMPRESSION RATIO	9.5:1	9.5:1
CLUTCH	Automatic	Automatic
TRANSMISSION	Five-speed automatic dual-clutch transmission with reverse and Low/Drive subtransmission	Five-speed automatic dual-clutch transmission with reverse and Low/Drive subtransmission
DRIVELINE	Direct front and rear driveshafts with TraxLok®; locking front differential	Direct front and rear driveshafts with TraxLok®; locking front differential
FRONT SUSPENSION	Independent double-wishbone; 7.3-inch travel	Independent double-wishbone; 7.3-inch travel
REAR SUSPENSION	Independent dual-arm; 8.5-inch travel	Independent dual-arm; 8.5-inch travel
FRONT BRAKES	Dual 190mm discs	Dual 190mm discs
REAR BRAKES	Dual 170mm discs	Dual 170mm discs
FRONT TIRES	25 x 8-12	25 x 8-12
REAR TIRES	25 x 10-12	25 x 10-12
LENGTH	86.0 inches	86.0 inches
WIDTH	47.4 inches	47.4 inches
HEIGHT	48.7 inches	48.7 inches
WHEELBASE	50.9 inches	50.9 inches
SEAT HEIGHT	36.3 inches	36.3 inches
TOWING CAPACITY	1322 pounds	1322 pounds
GROUND CLEARANCE	9.7 inches	9.7 inches
CURB WEIGHT	725 pounds (includes all standard equipment, required fluids and a full tank of fuel)	719 pounds (includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	3.9 gallons, including 1.3-gallon reserve	3.9 gallons, including 1.3-gallon reserve
FRONT RACK CAPACITY	99 pounds	99 pounds
REAR RACK CAPACITY	187 pounds	187 pounds