



# BUILT FOR WORK. BORN FOR WEEKENDS.

Some ATVs are built for a moment. The 2027 FourTrax Rancher lineup is built for the long haul — season after season, job after job, weekend after weekend. Known for durability, toughness, and Honda reliability, Rancher is the kind of machine you count on when plans change, and terrain doesn't cooperate. And with four trims to choose from, there's a Rancher that fits the way you work, ride, and live.



UTILITY ATVS ARE RECOMMENDED FOR RIDERS 16 YEARS AND OLDER. ATVS CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, BE RESPONSIBLE. READ THE OWNER'S MANUAL. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. BE CAREFUL ON DIFFICULT TERRAIN. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, ON PAVED SURFACES, ON PUBLIC ROADS, WITH PASSENGERS, OR AT EXCESSIVE SPEEDS. NO STUNT RIDING. RESPECT THE ENVIRONMENT WHEN RIDING. FourTrax®, Rancher®, Honda Pro-Connect™ and TraxLok®, TrueTimber Atera Camo® are registered trademarks of Honda Motor Co., Ltd. ©2026 American Honda Motor Co., Inc.


## 2027 FourTrax Rancher



### FourTrax Rancher




### FourTrax Rancher 4x4



### FourTrax Rancher 4x4 Automatic DCT EPS (Dual-clutch Transmission, Electric Power Steering)



### FourTrax Rancher 4x4 Automatic DCT IRS EPS (Dual-clutch Transmission, Independent Rear Suspension, Electric Power Steering)



## FEATURES & BENEFITS

### PROGRAMMED FUEL INJECTION

With a 34mm throttle body, 12-hole injector, and an oxygen sensor, the Programmed Fuel Injection (PGM-FI) promptly adjusts fuel mapping to ensure smooth operation, lower emissions, and enhanced fuel efficiency.

### FRONT/REAR CARGO RACKS

The driveshaft guards provide additional coverage for the front axles and outboard CV joints, illustrating another example of how Honda engineers focus on even the smallest details to create one of the best ATVs available.

### SHAFT DRIVE

The shaft drive is clean, low-maintenance, and efficient, making it the perfect choice for high-mileage riders. It eliminates the need for lubrication or adjustment while on the trail.

### WIDE FRONT DRIVESHAFT GUARDS

The driveshaft guards provide additional coverage for the front axles and outboard CV joints, illustrating another example of how Honda engineers focus on even the smallest details to create one of the best ATVs available.





# 2027 FourTrax Rancher



FourTrax Rancher



FourTrax Rancher 4X4

<b>ENGINE TYPE</b>	420cc longitudinally mounted liquid-cooled single-cylinder four-stroke	420cc longitudinally mounted liquid cooled single-cylinder four-stroke
<b>BORE AND STROKE</b>	86.5mm x 71.5mm	86.5mm x 71.5mm
<b>INDUCTION</b>	Programmed Fuel Injection (PGM-FI); 34mm throttle body	Programmed Fuel Injection (PGM-FI); 34mm throttle body
<b>VALVE TRAIN</b>	OHV; two valves per cylinder	OHV; two valves per cylinder
<b>COMPRESSION RATIO</b>	9.9:1	9.9:1
<b>STARTER</b>	Electric with optional auxiliary recoil	Electric with optional auxiliary recoil
<b>TRANSMISSION</b>	Five-speed with reverse	Five-speed with reverse
<b>DRIVELINE</b>	Direct rear driveshaft; two-wheel drive	Direct front and rear driveshafts with torque-biasing front differential
<b>FRONT SUSPENSION</b>	Independent double-wishbone; 6.7 inch travel	Independent double-wishbone; 6.7 inch travel
<b>REAR SUSPENSION</b>	Swingarm with single shock; 6.7-inch travel	Swingarm with single shock; 6.7-inch travel
<b>FRONT BRAKES</b>	Dual 190mm discs	Dual 190mm discs
<b>REAR BRAKE</b>	160mm sealed mechanical drum	160mm sealed mechanical drum
<b>FRONT TIRES</b>	24 x 8-12	24 x 8-12
<b>REAR TIRES</b>	24 x 10-11	24 x 10-11
<b>LENGTH</b>	82.8 inches	82.8 inches
<b>WIDTH</b>	47.4 inches	47.4 inches
<b>HEIGHT</b>	46.2 inches	46.2 inches
<b>WHEELBASE</b>	50.0 inches	50.0 inches
<b>SEAT HEIGHT</b>	33.7 inches	33.6 inches
<b>GROUND CLEARANCE</b>	7.1 inches	7.1 inches
<b>CURB WEIGHT</b>	580 pounds (Includes all standard equipment, required fluids and full tank of fuel)	615 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
<b>FUEL CAPACITY</b>	3.9 gallons	3.9 gallons
<b>FRONT RACK CAPACITY</b>	66 pounds	66 pounds
<b>REAR RACK CAPACITY</b>	133 pounds	133 pounds
<b>TURNING RADIUS</b>	9.2 feet	9.2 feet
<b>TOWING CAPACITY</b>	848 pounds	848 pounds

**One Year Included** Transferable, limited warranty

**Optional** Extended coverage available with a HondaCare® Protection Plan



# 2027 FourTrax Rancher



## FourTrax Rancher 4X4 Automatic DCT EPS

## FourTrax Rancher 4X4 Automatic DCT IRS EPS

<b>ENGINE TYPE</b>	420cc longitudinally mounted liquid-cooled single-cylinder four-stroke	420cc longitudinally mounted liquid cooled single-cylinder four-stroke
<b>BORE AND STROKE</b>	86.5mm x 71.5mm	86.5mm x 71.5mm
<b>INDUCTION</b>	Programmed Fuel Injection (PGM-FI); 34mm throttle body	Programmed Fuel Injection (PGM-FI); 34mm throttle body
<b>VALVE TRAIN</b>	OHV; two valves per cylinder	OHV; two valves per cylinder
<b>COMPRESSION RATIO</b>	9.9:1	9.9:1
<b>STARTER</b>	Electric with optional auxiliary recoil	Electric with optional auxiliary recoil
<b>TRANSMISSION</b>	Five-speed automatic Dual-Clutch Transmission (DCT) with reverse	Five-speed automatic Dual-Clutch Transmission (DCT) with reverse
<b>DRIVELINE</b>	Direct front and rear driveshafts with torque-biasing front differential	Direct front and rear driveshafts with torque-biasing front differential
<b>FRONT SUSPENSION</b>	Independent double-wishbone; 6.7 inch travel	Independent double-wishbone; 7.3 inch travel
<b>REAR SUSPENSION</b>	Swingarm with single shock; 6.7-inch travel	Independent dual-arm; 8.5 inch travel
<b>FRONT BRAKES</b>	Dual 190mm discs	Dual 193mm discs
<b>REAR BRAKE</b>	160mm sealed mechanical drum	Dual 170mm discs
<b>FRONT TIRES</b>	24 x 8-12	24 x 8-12
<b>REAR TIRES</b>	24 x 10-11	24 x 10-11
<b>LENGTH</b>	82.8 inches	84.5 inches
<b>WIDTH</b>	47.4 inches	47.4 inches
<b>HEIGHT</b>	46.2 inches	47.2 inches
<b>WHEELBASE</b>	50.0 inches	51.0 inches
<b>SEAT HEIGHT</b>	33.6 inches	35.4 inches
<b>GROUND CLEARANCE</b>	7.1 inches	9.6 inches
<b>CURB WEIGHT</b>	642 pounds (Includes all standard equipment, required fluids and full tank of fuel)	686 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
<b>FUEL CAPACITY</b>	3.9 gallons	3.9 gallons
<b>FRONT RACK CAPACITY</b>	66 pounds	66 pounds
<b>REAR RACK CAPACITY</b>	133 pounds	133 pounds
<b>TURNING RADIUS</b>	9.2 feet	11.5 feet
<b>TOWING CAPACITY</b>	848 pounds	848 pounds

**One Year Included** Transferable, limited warranty

**Optional** Extended coverage available with a HondaCare® Protection Plan