



ROAR PAST THE ORDINARY

Born to break free, the Honda Fury is a masterpiece of real-world performance and custom style. With a low, sleek chopper design, 1312cc V-Twin engine, and standard ABS, this bike doesn't just stand out – it roars past the ordinary into the extraordinary.



2025 Fury ABS

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL. AND NEVER USE THE STREET AS A RACETRACK. Fury® is a registered trademark of Honda Motor Co., LTD ©2024 American Honda Motor Co., Inc.

FEATURES & BENEFITS

CHOPPER STYLING

This bike redefines custom motorcycle design with its sleek teardrop fuel tank, innovative single-shock rear suspension system, and aluminum swingarm.

V-TWIN ENGINE

Our artfully crafted 1312cc, 52-degree V-Twin engine features a single-pin crankshaft and dual counter-balancers, generating abundant torque and epitomizing the big-twin experience.

LOW SEAT HEIGHT

The super-low 26.9-inch seat height seamlessly integrates with the slender, elongated tank for a harmonious union that elevates form and function.

SHAFT FINAL DRIVE

The shaft drive is beautifully woven into the overall design, adding a touch of refinement while reducing the amount of required maintenance.



Fury ABS



ADVENTURE GREEN

SPECIFICATIONS

ENGINE TYPE	— 1312cc liquid-cooled 52-degree V-twin four-stroke
BORE AND STROKE	— 89.5mm x 104.3mm
COMPRESSION RATIO	— 9.2:1
VALVE TRAIN	— SOHC; three valves per cylinder
INDUCTION	— PGM-FI, 38mm throttle body
TRANSMISSION	— Five-speed manual
FINAL DRIVE	— Shaft
FRONT SUSPENSION	— 45mm telescopic fork; 5.1-inch travel
REAR SUSPENSION	— Single shock with adjustable rebound damping and five-position spring-preload adjustability; 3.7-inch travel
FRONT BRAKE	— Single 336mm disc with twin-piston caliper; ABS
REAR BRAKE	— Single 296mm disc with single-piston caliper; ABS
FRONT TIRE	— 90/90-21
REAR TIRE	— 200/50-18
WHEELBASE	— 71.0 inches
RAKE	— 32.0°
TRAIL	— 3.6 inches
SEAT HEIGHT	— 26.7 inches
FUEL CAPACITY	— 3.4 gallons
CURB WEIGHT	— 675 pounds (Includes all standard equipment, required fluids and a full tank of fuel.)