




TWO WHEELS. ENDLESS FEELS.

The Navi is your gateway to two-wheeled freedom and fun. With its effortless twist-and-go automatic transmission, approachable design, and an “are-you-kidding-me?” price, it’s perfect for new riders or anyone craving adventure. Compact, stylish, and always a vibe, this miniMOTO delivers big fun without breaking the bank



2025 NAVI

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER USE THE STREET AS A RACETRACK. NAVI® is a registered trademarks of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.



NAVI

SPECIFICATIONS

ENGINE TYPE	— 109cc air-cooled single-cylinder four-stroke
BORE AND STROKE	— 55.0mm x 55.6mm
COMPRESSION RATIO	— 9.5:1
VALVE TRAIN	— OHC; two valves per cylinder
INDUCTION	— 16mm carburetor
TRANSMISSION	— V-Matic automatic CVT
FRONT SUSPENSION	— 26.6mm inverted telescopic fork; 3.5-inch travel
REAR SUSPENSION	— Single shock; 2.8-inch travel
FRONT BRAKE	— 130mm drum; Combined Braking System (CBS)
REAR BRAKE	— 130mm drum; Combined Braking System (CBS)
FRONT TIRE	— 90/90-12
REAR TIRE	— 90/100-10
WHEELBASE	— 50.6 inches
SEAT HEIGHT	— 30.0 inches
RAKE	— 27.5°
TRAIL	— 3.1 inches
FUEL CAPACITY	— 0.9 gallon, including 0.2-gallon reserve
CURB WEIGHT	— 234 pounds (Includes all standard equipment, required fluids and full tank of fuel)

FEATURES & BENEFITS

109cc FOUR-STROKE ENGINE

One of the best things about this bike is its reliable Honda engine. It's air-cooled for simplicity, offers great fuel efficiency, and makes plenty of power while also being low-maintenance and super dependable.

AUTOMATIC TRANSMISSION

The continuous variable transmission (CVT) requires no clutch or shifting. Simply start the vehicle, twist the throttle, and go. There is also no neutral or park mode.

LOW SEAT HEIGHT

A low, 30-inch seat height allows for easy mounting and flat-footing. And the long, flat seat makes finding the right riding position easy.

ELECTRIC STARTER

Starting the engine is a breeze with both an electric starter and a backup kickstarter.