

VERSATILITY IS ITS VIRTUE.

Versatility and a do-it-all attitude—that's what the Pioneer 1000-5 is all about. QuickFlip seats let you carry up to five people and fold flat for carrying cargo. The 999cc engine and automatic DCT transmission are an unbeatable combo. Three trims — including our new Special Edition this year — make it easy to pick one that's perfect for you.





2025 Pioneer 1000-5/ Deluxe/Trail/SE





Pioneer 1000-5











Pioneer 1000-5 Trail Special Edition

MATTE GRAY METALLIC

FEATURES & BENEFITS

CHASSIS AND SUSPENSION

Large tires, long-travel independent front and rear suspension, and our sophisticated driveline provide excellent handling and comfort.

POWERFUL 999cc TWIN-CYLINDER ENGINE

With plenty of power — especially in the midrange and top end — you'll experience quick acceleration and exceptional overall performance.

FULLY AUTOMATIC SIX-SPEED DCT

With the industry's first six-speed Dual-Clutch Transmission (DCT), you can choose between manual mode or fully automatic. There's even an easy-to-use tow/haul mode, along with 2WD, 4WD, Differential Lock, and Turf selections.

QUICKFLIP® SEATING

Two QuickFlip seats in the cargo bed open easily and fold flat when not in use. A Honda exclusive, the design helps offers better maneuverability on the trails.





	Pioneer 1000-5	Pioneer 1000-5 Deluxe
ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.2mm	92.0mm x 75.2mm
INDUCTION	Fuel Injection (PGM-FI);, 44mm throttle body	Fuel Injection (PGM-FI);, 44mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with reverse; four drive modes include 2WD, 4WD, Turf and Differential lock; Paddle Shifters with three shift modes (standard, sport, and manual)	Six-speed automatic Dual-Clutch Transmission (DCT) with reverse; four drive modes include 2WD, 4WD, Turf and Differential lock; Paddle Shifters with three shift modes (standard, sport, and manual)
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 10.6 inch travel	Independent double-wishbone; 10.6 inch travel
REAR SUSPENSION	Independent double-wishbone; 10.0 inch travel	Independent double-wishbone; 10.0 inch travel
FRONT BRAKES	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs
REAR BRAKES	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs
FRONT TIRES	27 x 9-14	27 x 9-14
REAR TIRES	27 x 11-14	27 x 11-14
LENGTH	116.9 inches	116.9 inches
WIDTH	62.8 inches	63.0 inches
HEIGHT	77.3 inches	76.3 inches
WHEELBASE	80.2 inches	80.2 inches
BED CAPACITY	1000 pounds for 49- state models; 600 pounds for CA models	1000 pounds for 49- state models; 600 pounds for CA models
SEAT HEIGHT	34.3 inches	33.8 inches
TOWING CAPACITY	2500 pounds	2500 pounds
GROUND CLEARANCE	13.2 inches	12,3 inches
CURB WEIGHT	1720 pounds (Includes all standard equipment, required fluids and full tank of fuel)	1728 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	7.9 gallons, including 1.2-gallon reserve	7.9 gallons, including 1.2-gallon reserve
TURNING RADIUS	13.8 feet	13.8 feet



	Pioneer 1000-5 Trail Special Edition
ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
RE AND STROKE	92.0mm x 75.2mm
NDUCTION	Fuel Injection (PGM-FI);, 44mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with reverse; four drive modes include 2WD, 4WD, Turf and Differential lock; Paddle Shifters with three shift modes (standard, sport, and manual)
DRIVELINE	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 10.5 inch travel
REAR SUSPENSION	Independent double-wishbone; 10.0 inch travel
FRONT BRAKES	Dual 210mm hydraulic discs
REAR BRAKES	Dual 210mm hydraulic discs
FRONT TIRES	27 x 9-14
REAR TIRES	27 x 11-14
LENGTH	119.2 inches
WIDTH	63.0 inches
HEIGHT	76.5 inches
WHEELBASE	80.2 inches
BED CAPACITY	1000 pounds for 49- state models; 600 pounds for CA models
SEAT HEIGHT	33.1 inches
TOWING CAPACITY	2500 pounds
GROUND CLEARANCE	12.3 inches
CURB WEIGHT	1777 pounds (Includes all standard equipment, required fluids and full tank of fuel)
FUEL CAPACITY	7.9 gallons, including 1.2-gallon reserve
TURNING RADIUS	13.8 feet