

POWER YOUR WILDEST JOURNEYS

When hard work and sheer joy collide, you get the Pioneer 1000 lineup. Renowned for their unwavering reliability and packed with features like our automatic Dual-Clutch Transmission (DCT), the Pioneer 1000 family comes in four trims and four colors for 2025 to perfectly match your needs. Drive one today and experience the Pioneer difference.



PIONEER 1000 IS ONLY FOR DRIVERS 16 YEARS AND OLDER, MULTI-PURPOSE UTILITY VEHICLES(SIDE BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY, ALWAYS WEAR A HELMET, EYE PROTECTION AND APPROPRIATE CLOTHING, ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. AVOID EXCESSIVE SPEEDS AND BE CAREFUL ON DIFFICULT TERRAIN. READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL, OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO HIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE HAND HOLD WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Pioneer® TrueTimber® Atera Camouflage, Unicam® and QuickFlip® are registered trademarks of Honda Motor Co., Ltd. ©2024 American Honda Motor Co., Inc.

2025 Pioneer 1000/ Deluxe/Forest/Trail





Pioneer 1000





Pioneer 1000 Deluxe





Pioneer 1000 Forest





Pioneer 1000 Trail

MATTE GREEN METALLIC



POWERFUL 999cc TWIN-CYLINDER ENGINE

The 1000 lineup has been designed with robust midrange and top-end power, which, thanks to the lower gear ratios, results in quick acceleration and exceptional overall performance.

AUTOMATIC SIX-SPEED DCT

The industry's first all-gear-driven six-speed automatic Dual-Clutch Transmission (DCT) allows you to choose between manual or fully automatic. Additionally, Sport mode increases the fun by holding the shift points to higher engine speeds.

2500-POUND TOWING CAPACITY

The 1000 lineup can haul up to 2500 pounds, making it possible to complete bigger jobs without having to use a tractor or a truck.

TURF/2WD/4WD/DIFF LOCK

To avoid damaging sensitive surfaces, make sure to select Turf Mode. If you require maximum traction, switch to 4WD. And if you need the most power from all four wheels, lock the front and rear differentials. The best part is that you can easily do all this with a single lever.





	7 18.1861 1886	. Islies. Isse Delake
ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm
INDUCTION	Fuel Injection (PGM-FI);, 44mm throttle body	Fuel Injection (PGM-FI);, 44mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with reverse; four drive modes include 2WD, 4WD, Turf and Differential lock; Paddle Shifters with three shift modes (standard, sport, and manual)	Six-speed automatic Dual-Clutch Transmission (DCT) with reverse; four drive modes include 2WD, 4WD, Turf and Differential lock; Paddle Shifters with three shift modes (standard, sport, and manual)
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 10.6 inch travel	Independent double-wishbone; 10.6 inch travel
REAR SUSPENSION	Independent double-wishbone; 10.0 inch travel	Independent double-wishbone; 10.0 inch travel
FRONT BRAKES	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs
REAR BRAKES	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs
FRONT TIRES	27 x 9-14	27 x 9-14
REAR TIRES	27 x 11-14	27 x 11-14
LENGTH	117.1 inches	117.1 inches
WIDTH	63.0 inches	63.0 inches
HEIGHT	76.9 inches	76.9 inches
WHEELBASE	80.2 inches	80.2 inches
BED CAPACITY	1000 pounds for 49- state models; 600 pounds for CA models	1000 pounds for 49- state models; 600 pounds for CA models
TOWING CAPACITY	2500 pounds	2500 pounds
GROUND CLEARANCE	13.6 inches	13.6 inches
CURB WEIGHT	1595 pounds (Includes all standard equipment, required fluids and full tank of fuel)	1598 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	7.9 gallons, including 1.7-gallon reserve	7.9 gallons, including 1.7-gallon reserve
TURNING RADIUS	13.8 feet	13.8 feet



ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm
INDUCTION	Fuel Injection (PGM-FI);, 44mm throttle body	Fuel Injection (PGM-FI);, 44mm throttle body
VALVE TRAIN	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with reverse; four drive modes include 2WD, 4WD, Turf and Differential lock; Paddle Shifters with three shift modes (standard, sport, and manual)	Six-speed automatic Dual-Clutch Transmission (DCT) with reverse; four drive modes include 2WD, 4WD, Turf and Differential lock; Paddle Shifters with three shift modes (standard, sport, and manual)
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 10.6 inch travel	Independent double-wishbone; 10.6 inch travel
REAR SUSPENSION	Independent double-wishbone; 10.0 inch travel	Independent double-wishbone; 10.0 inch travel
FRONT BRAKES	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs
REAR BRAKES	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs
FRONT TIRES	27 x 9-14	27 x 9-14
REAR TIRES	27 x 11-14	27 x 11-14
LENGTH	120.4 inches	120.4 inches
WIDTH	63.0 inches	63.0 inches
HEIGHT	76.1 inches	76.6 inches
WHEELBASE	80.2 inches	80,2 inches
BED CAPACITY	1000 pounds for 49- state models; 600 pounds for CA models	1000 pounds for 49- state models; 600 pounds for CA models
TOWING CAPACITY	2500 pounds	2500 pounds
GROUND CLEARANCE	12.8 inches	12.8 inches
CURB WEIGHT	1654 pounds (Includes all standard equipment, required fluids and full tank of fuel)	1676 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	7.9 gallons, including 1.7-gallon reserve	7.9 gallons, including 1.7-gallon reserve
TURNING RADIUS	13.8 feet	13.8 feet