



JOIN THE REBELLION

Pure cruiser cool, now even more accessible. The Rebel 300's lightweight design and new seat, handlebars, and rear suspension make every ride more comfortable and confident — whether you're a seasoned rider or just starting out. And with two new colorways, Matte Black Metallic and Pearl Smoky Gray, it looks as good as it goes.



2025 Rebel 300/ABS

ALWAYS WEAR A HELMET, EYE PROTECTION, AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. Rebel® is a registered trademark of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.



Rebel 300



 MATTE BLACK METALLIC



 PEARL SMOKY GRAY

 MATTE BLACK METALLIC

FEATURES & BENEFITS

SPORTY ENGINE

The compact single-cylinder engine features fuel injection, dual cams, and counterbalancing — perfectly designed to fit your journey with its lightweight build and torque-rich power delivery.

LOW SEAT HEIGHT

In the realm of cruiser seat heights, lower reigns supreme. This bike flaunts one of the lowest at 27.2 inches for maximum rider comfort and easy flat-footing at lights or in parking lots.

BLACKED-OUT STYLE

The Rebel is ready for you to unleash your creativity. It's a canvas of self-expression that's impressive by day and a masterpiece at night.

REVISED REAR SUSPENSION

Equipped with custom spring rates, the rear shocks get redesigned internals for increased bottoming resistance, added comfort, and improved handling.





2025 Rebel 300/ABS



Rebel 300



Rebel 300 ABS

	Rebel 300	Rebel 300 ABS
ENGINE TYPE	286cc liquid-cooled single-cylinder four-stroke	286cc liquid-cooled single-cylinder four-stroke
BORE AND STROKE	76.0mm x 63.0mm	76.0mm x 63.0mm
INDUCTION	Programmed Fuel Injection (PGM-FI); 38mm throttle body	Programmed Fuel Injection (PGM-FI); 38mm throttle body
VALVE TRAIN	DOHC; four valves per cylinder	DOHC; four valves per cylinder
COMPRESSION RATIO	10.7:1	10.7:1
FINAL DRIVE	O-ring-sealed chain; 14T/36T	O-ring-sealed chain; 14T/36T
TRANSMISSION	Six-speed manual w/slipper clutch	Six-speed manual w/slipper clutch
FRONT SUSPENSION	41mm fork; 4.8-inch travel	41mm fork; 4.8-inch travel
REAR SUSPENSION	Dual shocks; 3.7-inch travel	Dual shocks; 3.7-inch travel
FRONT BRAKES	Single 296mm disc	Single 296mm disc; ABS
REAR BRAKES	Single 240mm disc	Single 240mm disc; ABS
FRONT TIRES	130/90-16	130/90-16
REAR TIRES	150/80-16	150/80-16
RAKE	28.0°	28.0°
TRAIL	4.3 inches	4.3 inches
WHEELBASE	58.6 inches	58.7 inches
SEAT HEIGHT	27.2 inches	27.2 inches
CURB WEIGHT	364 pounds (Includes all standard equipment, required fluids and a full tank of fuel)	379 pounds (includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	3.0 gallons	3.0 gallons

One Year Included Transferable, unlimited-mileage warranty

Optional Extended Extended coverage available with a HondaCare® Protection Plan