



FROM FIRST RIDE TO FOREVER RIDE

Rebel 500 makes every ride approachable, fun, and stylish — now with ABS standard on every model. Choose the classic 500 or the factory-custom SE — either way, this lightweight cruiser is a canvas for your style, with a proven parallel-twin engine, easy handling, and the confidence to explore the open road.



2026 Rebel 500/ Special Edition

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. Rebel® is a registered trademark of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.



Rebel 500



PEARL SMOKY GRAY
PEARL BLACK

Rebel 500 Special Edition



PEARL BLUE

FEATURES & BENEFITS

DISC BRAKES WITH ABS

Front and rear disc brakes with our Anti-Lock Braking System (ABS) now come standard on all trims, giving you excellent linear stopping power for supreme confidence in even the most challenging conditions.

SPORTY ENGINE

Celebrated for its versatility, the narrow parallel-twin engine masters size reduction while delivering big low-rpm torque and thrilling high-rpm performance.

LOW SEAT HEIGHT

In the realm of cruiser seat heights, lower reigns supreme. This bike flaunts one of the lowest at 27.2 inches for maximum rider comfort and easy flat-footing at lights or in parking lots.

PREMIUM REAR SUSPENSION

Equipped with pre-load adjustable rear shocks and custom spring rates, the suspension provides the perfect blend of comfort and performance, elevating your riding experience.





2026 Rebel 500/ Special Edition



Rebel 500

Rebel 500 Special Edition

ENGINE TYPE	471cc liquid-cooled parallel-twin four-stroke	471cc liquid-cooled parallel-twin four-stroke
BORE AND STROKE	67.0mm x 66.8mm	67.0mm x 66.8mm
INDUCTION	Programmed Fuel Injection system (PGM-FI); 34mm throttle body	Programmed Fuel Injection system (PGM-FI); 34mm throttle body
VALVE TRAIN	DOHC; four valves per cylinder	DOHC; four valves per cylinder
COMPRESSION RATIO	10.7:1	10.7:1
FINAL DRIVE	O-ring-sealed chain; 15T/40T	O-ring-sealed chain; 15T/40T
TRANSMISSION	Six-speed manual with slipper clutch	Six-speed manual with slipper clutch
FRONT SUSPENSION	41mm fork; 5.5-inch travel	41mm fork; 5.5-inch travel
REAR SUSPENSION	Dual shocks; 3.7-inch travel	Dual shocks; 3.7-inch travel
FRONT BRAKES	Single 296.0mm disc; ABS	Single 296mm disc; ABS
REAR BRAKES	Single 240.0mm disc; ABS	Single 240mm disc; ABS
FRONT TIRES	130/90-16	130/90-16
REAR TIRES	150/80-16	150/80-16
RAKE	28.0°	28.0°
TRAIL	4.3 inches	4.3 inches
WHEELBASE	58.7 inches	58.7 inches
SEAT HEIGHT	27.2 inches	27.2 inches
CURB WEIGHT	414 pounds (Includes all standard equipment, required fluids and a full tank of fuel)	419 pounds (includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	3.0 gallons	3.0 gallons