



# ADVENTURE, AMPLIFIED

The Talon 1000R isn't just a side-by-side – it's a high-performance powerhouse for two. With our exclusive 999cc Unicam® engine, automatic Dual-Clutch Transmission, and available FOX Live Valve advanced semi-active suspension, you'll dominate wide-open terrain with next-level power and control.

TALONS ARE ONLY FOR DRIVERS 16 YEARS AND OLDER. MULTI-PURPOSE UTILITY VEHICLES (SIDE-BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY. ALWAYS WEAR A HELMET, EYE PROTECTION, APPROPRIATE CLOTHING AND READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL, OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO FIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE GRAB BAR WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Talon® is a registered trademark of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.



# 2025 Talon 1000R Fox Live Valve



**Talon 1000R**



  
MATTE ABYSS BLACK



**Talon 1000R  
Fox Live Valve**

  
MATTE NAVY BLUE  
  
PEARL RED

## FEATURES & BENEFITS

### POWERFUL 999cc TWIN-CYLINDER ENGINE

Experience unparalleled power with our liquid-cooled 999cc inline-twin engine, boasting high horsepower, ample torque, and unmatched refinement throughout the rpm range.

### AUTOMATIC SIX-SPEED DCT

Our automatic Dual-Clutch Transmission (DCT) boasts a class-leading gear-driven setup, giving you manual or automatic control. It has efficient power delivery, true engine braking, and superior performance compared to belt-driven CVTs.

### FULL-COVERAGE HARD DOORS

Hard doors are standard, offering full coverage and excellent weather protection. They provide extra storage space with cupholders and secure compartments. Doors use a double-latch design that's rattle-free.

### WEIGHT BIAS

A slight rear weight bias works best for optimal sport driving. This is why we set up the Talons with 44% of their weight over the front and 56% over the rear.





# 2025 Talon 1000RS / Fox Live Valve



**Talon 1000R**

**Talon 1000R Fox Live Valve**

<b>ENGINE TYPE</b>	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
<b>BORE AND STROKE</b>	92.0mm x 75.1mm	92.0mm x 75.1mm
<b>INDUCTION</b>	Fuel Injection (PGM-FI);, 46mm throttle body	Fuel Injection (PGM-FI);, 46mm throttle body
<b>VALVE TRAIN</b>	Unicam® SOHC; four valves per cylinder	Unicam® SOHC; four valves per cylinder
<b>COMPRESSION RATIO</b>	10:1	10:1
<b>TRANSMISSION</b>	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/paddle shifters)	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/ paddle shifters)
<b>DRIVELINE</b>	Direct front and rear driveshafts	Direct front and rear driveshafts
<b>FRONT SUSPENSION</b>	Independent double-wishbone with Showa® shocks; 17.6 inch travel	Independent double-wishbone with FOX Live Valve shocks; 17.7-inch travel
<b>REAR SUSPENSION</b>	4+ link trailing arm; with Showa shocks 20.1-inch travel	4+ link trailing arm with FOX Live Valve shocks; 20.1-inch travel
<b>FRONT BRAKES</b>	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
<b>REAR BRAKES</b>	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
<b>FRONT TIRES</b>	28 x 9-15	28 x 9-15
<b>REAR TIRES</b>	28 x 11-15	28 x 11-15
<b>LENGTH</b>	123.7 inches	123.7 inches
<b>WIDTH</b>	68.1 inches	68.1 inches
<b>HEIGHT</b>	75.8 inches	75.8 inches
<b>WHEELBASE</b>	90.0 inches	90.0 inches
<b>BED CAPACITY</b>	299 pounds	299 pounds
<b>SEAT HEIGHT</b>	28.3 inches	28.3 inches
<b>GROUND CLEARANCE</b>	13.2 inches	13.2 inches
<b>CURB WEIGHT</b>	1601 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1596 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel	1592 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1592 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel
<b>FUEL CAPACITY</b>	7.3 gallons, including 1.1-gallon reserve	7.7 gallons, including 1.1-gallon reserve
<b>TURNING RADIUS</b>	19.4 feet	19.4 feet