



Talon 1000X-4/1000X-4 FOX Live Valve/ Special Edition

MORE WAYS TO SHARE THE FUN

One of the best parts of any side-by-side is sharing the fun with friends and family. And that's where Honda's Talon® 1000X-4 models really shine. With four seats, there's room for the whole crew. But here's the biggest difference these four seat side-by-sides are done the Honda way, so those extra passengers get stadium seating and plush accommodations. Plus, there are three models to chose from: The Talon 1000X-4 features FOX Podium shocks with QS3 manual adjustors, while the Talon 1000X-4 FOX Live Valve comes with a radical, self-adjusting suspension. Plus, Talon 1000X-4 FOX Live Valve owners get some tasty extra features, like Honda's launch mode. And new for 2021, check out our Talon 1000X-4 Special Edition, with some of your favorite options and accessories pre-installed for more added adventure and exploration.

TALONS ARE ONLY FOR DRIVERS 16 YEARS AND OLDER. MULTI-PURPOSE UTILITY VEHICLES (SIDE-BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY. ALWAYS WEAR A HELMET, EVE PROTECTION, APPROPRIATE CLOTHING AND READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL, OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO FIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE GRAB BAR WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Talon® is a registered trademark of Honda Motor Co., Ltd. #2021 American Honda Motor Co., Inc







Talon 1000X-4







PEARL WHITE



Talon 1000X-4 Special Edition



FEATURES & BENEFITS



POWERFUL 999cc TWIN-CYLINDER ENGINE

The Talon's 999cc liquid-cooled inline twin delivers the kind of powerful torque and quick-revving horsepower you'd expect from a flagship sport model, but is equally responsive in lower revs and in the critical midrange too. Set longitudinally in the chassis, it delivers the kind of refinement no other side-by-side can match.



AUTOMATIC SIX-SPEED DCT TRANSMISSION

The convenience of an automatic with the strength, control, and efficiency of a manual, Honda's Dual-Clutch Transmission (DCT) lets you drive the way you want. Choose between manual mode or fully automatic. In addition, you also get genuine compression braking and a more efficient power delivery than a belt-driven CVT.



FOX LIVE VALVE SUSPENSION

The Talon 1000X-4 FOX Live Valve features FOX Live Valve suspension with 2.5-inch shocks on all four wheels. The system adjusts damping on each shock independently, automatically, and up to 200 times a second for superior ride quality and less pitch and roll over all terrain.



CUSTOMIZED THE WAY YOU LIKE

This year we're offering a Special Edition version. It's fully outfitted from the factory with a warn 3,500 lb. winch, front bumper, full poly vented windscreen, 40" LED light bar, accessory switch plate hard roofs and lower door panels, special Camo graphics, and more, all pre-installed.Instant gratification, and a solid deal, too.

Life is better on a Honda

2021 TALON 1000X-4



Talon 1000X-4



Talon 1000X-4 Fox Live Valve



Talon 1000X-4 Special Edition

ENGINE TYPE	999cc liquid-cooled Unicam® OHC longitudinally mounted parallel-twin four-stroke; four valves per cylinder	999cc liquid-cooled Unicam OHC longitudinally mounted parallel-twin four-stroke; four valves per cylinder	999cc liquid-cooled Unicam OHC longitudinally mounted parallel-twin four-stroke; four valves per cylinder
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm	92.0mm x 75.1mm
COMPRESSION RATIO	10:1	10:1	10:1
INDUCTION	Fuel Injection (PGM-FI), 46mm throttle body	Fuel Injection (PGM-FI), 46mm throttle body	Fuel Injection (PGM-FI), 46mm throttle body
IGNITION	Full-transistorized with electronic advance	Full-transistorized with electronic advance	Full-transistorized with electronic advance
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission. Two drive modes with 2WD and i-4WD. Three shift modes (standard, sport, manual w/ paddle shifters).	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission. Two drive modes with 2WD and i-4WD. Three shift modes (standard, sport, manual w/ paddle shifters).	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission. Two drive modes with 2WD and i-4WD. Three shift modes (standard, sport, manual w/ paddle shifters).
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 14.4 inches of travel	Independent double-wishbone; 14.6 inches of travel	Independent double-wishbone; 14.6 inches of trave
REAR SUSPENSION	3-link trailing arm; 15.0 inches of travel	3-link trailing arm; 15.0 inches of travel	3-link trailing arm; 15.0 inches of travel
FRONT BRAKE	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs	Dual 210mm hydraulic discs
REAR BRAKE	Dual 210mm hydraulic disc	Dual 210mm hydraulic disc	Dual 210mm hydraulic disc
FRONT TIRES	28 x 9-15	28 x 9-15	28 x 9-15
REAR TIRES	28 x 11-15	28 x 11-15	28 x 11-15
LENGTH	152.6 inches	152.6 inches	154.3 inches
WIDTH	64.0 inches	64.0 inches	64.0 inches
HEIGHT	78.5 inches	78.1 inches	78.1 inches
WHEELBASE	116.4 inches	116.4 inches	116.4 inches
BED CAPACITY	299 pounds	299 pounds	299 pounds
GROUND CLEARANCE	12.8 inches	12.6 inches	12.6 inches
CURB WEIGHT	1735 pounds for 49 states - Includes all standard equipment, required fluids and full tank of fuel	1753 pounds for 49 states - Includes all standard equipment, required fluids and full tank of fuel	1831 pounds for 49 states - Includes all standard equipment, required fluids and full tank of fuel
CURB WEIGHT	1739 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel.	1755 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel.	1833 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel.
FUEL CAPACITY	7.7 gallons, including 0.9-gallon reserve	7.7 gallons, including 0.9-gallon reserve	7.7 gallons, including 0.9-gallon reserve
TURNING RADIUS	21.3 feet	21.3 feet	21.3 feet