



ADVENTURE IS BEST SHARED

The Talon 1000X-4 is your ticket to shared adventure on tight trails and technical terrain. With room for four, it's powered by our legendary 999cc Unicam® engine, smooth automatic Dual-Clutch Transmission, and available FOX Live Valve suspension for unmatched handling and control. Precision performance meets family-friendly fun — because adventure is better together.



2025 Talon 1000X-4 Fox Live Valve

TALONS ARE ONLY FOR DRIVERS 16 YEARS AND OLDER. MULTI-PURPOSE UTILITY VEHICLES (SIDE-BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY. ALWAYS WEAR A HELMET, EYE PROTECTION, APPROPRIATE CLOTHING AND READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL, OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO FIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE GRAB BAR WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Talon® is a registered trademark of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.



Talon 1000X-4




MATTE ABYSS BLACK

**Talon 1000X-4
Fox Live Valve**




MATTE NAVY BLUE

PEARL RED

FEATURES & BENEFITS

POWERFUL 999cc TWIN-CYLINDER ENGINE

Experience unparalleled power with our liquid-cooled 999cc Unicam inline-twin engine, boasting high horsepower, big torque, and unmatched refinement and reliability throughout the rpm range.

DRIVER AND PASSENGER PROTECTION

Safety is our top priority. The standard roof and hard doors with side nets help protect from debris and keep occupants inside. Three-point seatbelts and emergency locking retractors provide added safety.

AUTOMATIC SIX-SPEED DCT

Our automatic Dual-Clutch Transmission (DCT) boasts a class-leading gear-driven setup, giving you manual or automatic control. It has efficient power delivery, true engine braking, and superior performance to belt-driven CVTs

STADIUM SEATING

Welcome to the best seats in the house: Because they sit nearly three inches higher and two inches closer to each other than the fronts, the rear "Stadium Seating" lets passengers see more. Enjoy the view!





2025 Talon 1000X-4 / Fox Live Valve



Talon 1000X-4

Talon 1000X-4 Fox Live Valve

ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm
INDUCTION	Fuel Injection (PGM-FI); 46mm throttle body	Fuel Injection (PGM-FI); 46mm throttle body
VALVE TRAIN	Unicam® SOHC; four valves per cylinder	Unicam® SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/paddle shifters)	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/ paddle shifters)
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 14.6 inch travel	Independent double-wishbone with FOX Live Valve shock absorbers; 14.4-inch travel
REAR SUSPENSION	4+ link trailing arm; 15.0-inch travel	4+ link trailing arm with FOX Live Valve shock absorbers; 15.0-inch travel
FRONT BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
REAR BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
FRONT TIRES	28 x 9-15	28 x 9-15
REAR TIRES	28 x 11-15	28 x 11-15
LENGTH	152.5 inches	152.5 inches
WIDTH	64.0 inches	64.0 inches
HEIGHT	78.2 inches	78.2 inches
WHEELBASE	116.4 inches	116.4 inches
BED CAPACITY	299 pounds	299 pounds
SEAT HEIGHT	28.0 inches	28.0 inches
GROUND CLEARANCE	12.8 inches	12.4 inches
CURB WEIGHT	1792 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1797 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel	1797 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1797 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel
FUEL CAPACITY	7.7 gallons, including 0.9-gallon reserve	7.7 gallons, including 0.9-gallon reserve
TURNING RADIUS	21.7 feet	21.7 feet