



EXPLORE BEYOND: TALON AWAITS

Engineered with precision, this powerhouse sport side-by-side redefines off-road adventures. At its heart beats a robust 999cc liquid-cooled engine, and coupled with Honda's pioneering automatic DCT, transforms every journey into an exhilarating escape. Embrace the freedom to explore, to challenge, to master the wilderness. The Talon 1000X and 1000X FOX Live Valve aren't just vehicles; they're your ticket to the extraordinary.



2024 Talon 1000X Fox Live Valve

TALONS ARE ONLY FOR DRIVERS 16 YEARS AND OLDER. MULTI-PURPOSE UTILITY VEHICLES (SIDE-BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY. ALWAYS WEAR A HELMET, EYE PROTECTION, APPROPRIATE CLOTHING AND READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL, OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO FIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE GRAB BAR WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Talon® is a registered trademark of Honda Motor Co., Ltd. ©2024 American Honda Motor Co., Inc.



Talon 1000X




MATTE ABYSS BLACK

**Talon 1000X
Fox Live Valve**




MATTE NAVY BLUE

PEARL RED

FEATURES & BENEFITS

POWERFUL 999cc TWIN-CYLINDER ENGINE

Unleash ample power with the 999cc liquid-cooled inline twin engine. It produces big torque, high horsepower, and responsiveness across the rpm range, the result of unmatched refinement and reliability.

FOX LIVE VALVE SUSPENSION

The cutting-edge semi-active suspension utilizes FOX's adaptive Live Valve technology, dynamically adjusting compression damping for each wheel. Enjoy reduced body roll, smoother terrain navigation, and superior resistance to bottoming for the ultimate deluxe ride.

AUTOMATIC SIX-SPEED DCT TRANSMISSION

Convenience and prowess converge with our automatic Dual-Clutch Transmission (DCT), with its class-leading gear-driven setup giving you the option for manual or fully automatic, it delivers true engine braking and efficient power delivery.

DRIVER/PASSENGER PROTECTION

The Occupant Protection Structure uses large-diameter tubing and meets ISO's rollover protection standard. Hard doors and quick-clip side nets help keep out debris, while auto-style three-point seatbelts feature an emergency locking retractor mechanism.





2024 Talon 1000X / Fox Live Valve



Talon 1000X



Talon 1000X Live Valve

ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm
INDUCTION	Fuel Injection (PGM-FI); 46mm throttle body	Fuel Injection (PGM-FI); 46mm throttle body
VALVE TRAIN	Unicam® SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/paddle shifters)	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/ paddle shifters)
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 14.6 inch travel	Independent double-wishbone with FOX Live Valve shock absorbers; 14.4-inch travel
REAR SUSPENSION	3-link trailing arm; 15.1-inch travel	4+ link trailing arm with FOX Live Valve shocks; 15.0-inch travel
FRONT BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
REAR BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
FRONT TIRES	28 x 9-15	28 x 9-15
REAR TIRES	28 x 11-15	28 x 11-15
LENGTH	123.7 inches	123.7 inches
WIDTH	64.0 inches	64.0 inches
HEIGHT	75.6 inches	75.4 inches
WHEELBASE	87.6 inches	87.6 inches
BED CAPACITY	299 pounds	299 pounds
SEAT HEIGHT	28.0 inches	28.0 inches
GROUND CLEARANCE	12.8 inches	12.8 inches
CURB WEIGHT	1545 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1550 pounds for CA models -Includes all standard equipment, required fluids and full tank of fuel	1552 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1554 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel
FUEL CAPACITY	7.3 gallons, including 1.1-gallon reserve	7.3 gallons, including 1.1-gallon reserve
TURNING RADIUS	17.7 feet	17.7 feet