

IT'S TALON TIME

The Talon 1000X is built for conquering tight trails and technical terrain with ease. Its shorter wheelbase and narrower stance deliver unmatched agility, while the 999cc Unicam® engine and automatic Dual-Clutch Transmission provide power and precision. With available FOX Live Valve semi-active suspension, it's your perfect partner for adventure in the woods and beyond.



TALONS ARE ONLY FOR DRIVERS 16 YEARS AND OLDER, MULTI-PURPOSE UTILITY VEHICLES (SIDE BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY, ALWAYS WEAR A HELMET, EYE PROTECTION, APPROPRIATE CLOTHING AND READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL., OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO FIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE GRAB BAR WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Talon® is a registered trademark of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.

2025 Talon 1000X Fox Live Valve



HONUP

Talon 1000X





Talon 1000X Fox Live Valve



FEATURES & BENEFITS

POWERFUL 999cc TWIN-CYLINDER ENGINE

Experience unparalleled power with our liquid-cooled 999cc inline-twin engine, boasting high horsepower, ample torque, and unmatched refinement throughout the rpm range.

AUTOMATIC SIX-SPEED DCT

Our automatic Dual-Clutch Transmission (DCT) boasts a class-leading gear-driven setup, giving you manual or automatic control. It has efficient power delivery, true engine braking, and superior performance compared to belt-driven CVTs.

FULL-COVERAGE HARD DOORS

Hard doors are standard, offering full coverage and excellent weather protection. They provide extra storage space with cupholders and secure compartments.

Doors use a double-latch design that's rattle-free

SHORTER WHEELBASE

The 87.6-inch wheelbase contributes to this sport side-by-side's tracking while also giving you a supersmooth ride. At 64 inches wide and shorter than the Talon 1000R, the Talon 1000X emphasizes quick handling and maneuverability.





ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm
INDUCTION	Fuel Injection (PGM-FI); 46mm throttle body	Fuel Injection (PGM-FI); 46mm throttle body
VALVE TRAIN	Unicam® SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/paddle shifters)	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/ paddle shifters)
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone with Showa shocks; 14.6-inch travel	Independent double-wishbone with FOX Live Valve shock absorbers; 14.4-inch travel
REAR SUSPENSION	3-link trailing arm; 15.1-inch travel	4+ link trailing arm with FOX Live Valve shocks; 15.0-inch travel
FRONT BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
REAR BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
FRONT TIRES	28 x 9-15	28 x 9-15
REAR TIRES	28 x 11-15	28 x 11-15
LENGTH	123.7 inches	123.7 inches
WIDTH	64.0 inches	64.0 inches
HEIGHT	75.6 inches	75.4 inches
WHEELBASE	87.6 inches	87.6 inches
BED CAPACITY	299 pounds	299 pounds
SEAT HEIGHT	28.0 inches	28.0 inches
GROUND CLEARANCE	12.8 inches	12.8 inches
CURB WEIGHT	1552 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1550 pounds for CA models -Includes all standard equipment, required fluids and full tank of fuel	1554 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1554 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel
FUEL CAPACITY	7.3 gallons, including 1.1-gallon reserve	7.3 gallons, including 1.1-gallon reserve
TURNING RADIUS	17.7 feet	17.7 feet