



## TIGHT TRAILS? NO PROBLEM!

Because you know your riding terrain better than anyone, we give you a choice when it comes to our Honda Talon models. The Talon 1000X is built for tight trails and technical terrain. Its shorter wheelbase and narrower stance deliver unmatched agility. But when it comes to the drivetrain, it's all about performance: the 999cc Unicam® engine and automatic Dual-Clutch Transmission provide the predictable power you need. And make sure you check out our Talon 1000X FOX Live Valve model too, offering semi-active suspension which automatically adjusts for precise handling and an unmatched ride over any terrain.

TALONS ARE ONLY FOR DRIVERS 16 YEARS AND OLDER. MULTI-PURPOSE UTILITY VEHICLES (SIDE-BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY. ALWAYS WEAR A HELMET, EYE PROTECTION, APPROPRIATE CLOTHING AND READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL, OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO FIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE GRAB BAR WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Talon® is a registered trademark of Honda Motor Co., Ltd. ©2026 American Honda Motor Co., Inc.



## 2026 Talon 1000X/ FOX Live Valve



**Talon 1000X**



**Talon 1000X  
FOX Live Valve**



## **FEATURES & BENEFITS**

### **POWERFUL 999cc TWIN-CYLINDER ENGINE**

You'll experience unparalleled power with our liquid-cooled 999cc parallel-twin engine, boasting high horsepower, ample torque, and unmatched refinement throughout the rpm range.

### **AUTOMATIC SIX-SPEED DCT**

Our automatic Dual-Clutch Transmission (DCT) boasts a class-leading gear-driven setup, giving you manual or automatic control. It has efficient power delivery, true engine braking, and superior performance compared to belt-driven CVTs.

### **FULL-COVERAGE HARD DOORS**

Hard doors are standard, offering full coverage and excellent weather protection. They provide extra storage space with cupholders and secure compartments. Doors use a double-latch design that's rattle-free.

### **SHORTER WHEELBASE**

The 87.6-inch wheelbase contributes to this sport side-by-side's tracking while also giving you a super-smooth ride. At 64 inches wide and shorter than the Talon 1000R, the Talon 1000X emphasizes quick handling and maneuverability.





# 2026 Talon 1000X / FOX Live Valve



Talon 1000X



Talon 1000X FOX Live Valve

ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm
INDUCTION	Fuel Injection (PGM-FI); 46mm throttle body	Fuel Injection (PGM-FI); 46mm throttle body
VALVE TRAIN	Unicam® SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic DCT	Six-speed automatic DCT; i4WD
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone with Showa shocks; 14.6-inch travel	Independent double-wishbone with FOX Live Valve shock absorbers; 14.6-inch travel
REAR SUSPENSION	3-link trailing arm; 15.1-inch travel	4+ link trailing arm with FOX Live Valve shocks; 15.1-inch travel
FRONT BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
REAR BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
FRONT TIRES	28 x 9-15	28 x 9-15
REAR TIRES	28 x 11-15	28 x 11-15
LENGTH	123.7 inches	123.7 inches
WIDTH	64.0 inches	64.0 inches
HEIGHT	75.4 inches	75.4 inches
WHEELBASE	87.6 inches	87.6 inches
BED CAPACITY	297 pounds	297 pounds
SEAT HEIGHT	28.0 inches	28.0 inches
GROUND CLEARANCE	12.8 inches	12.8 inches
CURB WEIGHT	1565 pounds- Includes all standard equipment, required fluids, and a full fuel tank.	1587 pounds- Includes all standard equipment, required fluids, and a full fuel tank.
FUEL CAPACITY	7.3 gallons, including 1.1-gallon reserve	7.3 gallons, including 1.1-gallon reserve
TURNING RADIUS	17.7 feet	17.7 feet