

# **RIDE ANYWHERE**

The XR<sup>™</sup>650L is one of the most honest, straightforward motorcycles on the planet—which is why it has such a huge following. Everything about this bike is rugged, simple, and proven: the air-cooled single-cylinder engine, the strong steel frame, the long-travel suspension. Electric starting and street-legal features make it a terrific commuter. We gave it some graphic updates last year that make it look even better (black rims, black seat, tool bag, fork boots, and white-on-white bodywork). It's a refreshingly straightforward bike in an increasingly complex world. And it's ready for any adventure you have in mind.



ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. AND PLEASE RESPECT THE ENVIRONMENT. XR<sup>™</sup>, Pro-Link<sup>®</sup>, and RFVC<sup>™</sup> are registered trademarks of Honda Motor Co., Ltd. Showa<sup>®</sup> is a registered trademark of Showa Mfg., Inc. ©2023 American Honda Motor Co., Inc.

# **2023 XR650L**





## SPECIFICATIONS

| ENGINE TYPE       | - | 644cc air-cooled dry-sump single-cylinder four-stroke                               |
|-------------------|---|---|
| BORE AND STROKE   | - | 100.0mm x 82.0mm  |
| COMPRESSION RATIO | _ | 8.3:1   |
| VALVE TRAIN       | _ | SOHC; four-valve RFVC™  |
| INDUCTION         | _ | 42.5mm diaphragm-type CV carburetor   |
| TRANSMISSION      | - | Five-speed  |
| FINAL DRIVE       | - | #520 O-ring sealed chain; 15T/45T   |
| FRONT SUSPENSION  | - | 43mm air-adjustable axle Showa® cartridge fork with 16-position compression-        |
|                   |   | damping adjustability; 11.6-inch travel   |
| REAR SUSPENSION   | - | Pro-Link Showa single-shock with spring-preload, 20-position compression            |
|                   |   | -and 20-position rebound-damping adjustability; 11.0-inch travel                    |
| FRONT BRAKE       | - | Single 256mm disc with twin-piston caliper  |
| REAR BRAKE        | - | Single 220mm disc   |
| FRONT TIRE        | - | 3.00-21   |
| REAR TIRE         | - | 4.60-18   |
| WHEELBASE         | - | 57.3 inches   |
| RAKE              | - | 27.0°   |
| TRAIL             | - | 4.0 inches  |
| SEAT HEIGHT       | - | 37.0 inches   |
| GROUND CLEARANCE  | - | 13.0 inches   |
| FUEL CAPACITY     | - | 2.8 gallons, including 0.6-gallon reserve   |
| CURB WEIGHT       | - | 346 pounds (Includes all standard equipment, required fluids and full tank of fuel) |

#### **FEATURES & BENEFITS**

#### FOUR-STROKE ENGINE

The XR650L's four-stroke, single-cylinder engine offers good fuel efficiency and a wide powerband. In addition, its proven powerplant requires very little maintenance.

## **ELECTRIC STARTER**

Adventure is just the push of a button away. The XR650L's electric starter takes all the drama out of restarting offroad, or getting underway on a cold morning or after the bike's been sitting all week.

#### STREET-LEGAL FEATURES

Fully equipped for the street—including turn signals, license-plate light, mirrors, speedometer and more. There's even a grab strap and footpegs for a passenger.

# SEALED-BATTERY

No maintenance hassles here, even in the case of an offroad tip over. The sealed battery has plenty of cranking power for the electric starter, and is well protected from the vibrations of off-road riding

