

Compare motorcycles



2025 Gold Wing 50th Anniversary



2025 Gold Wing DCT 50th Anniversary



2025 Gold Wing Tour

ENGINE				
Engine Type	Engine Type	Engine Type		
1833cc liquid-cooled horizontally opposed six-cylinder	1833cc liquid-cooled horizontally opposed six-cylinder	1833cc liquid-cooled horizontally opposed six-cylinder		
four-stroke	four-stroke	four-stroke		
Bore And Stroke	Bore And Stroke	Bore And Stroke		
73.0 mm x 73.0 mm	73.0 mm x 73.0 mm	73.0 mm x 73.0 mm		
Compression Ratio	Compression Ratio	Compression Ratio		
10.5:1	10.5:1	10.5:1		
Valve Train	Valve Train	Valve Train		
Unicam® SOHC; four valves per cylinder	Unicam® SOHC; four valves per cylinder	Unicam® SOHC; four valves per cylinder		
Induction	Induction	Induction		
Programmed Fuel Injection (PGM-FI); 50.0 mm throttle	Programmed Fuel Injection (PGM-FI); 50.0 mm throttle	Programmed Fuel Injection (PGM-FI); 50.0 mm throttle		
body	body	body		

	DRIVETRAIN	
Transmission	Transmission	Transmission
Six-speed manual	Seven-speed Automatic Dual-Clutch Transmission	Six-speed manual
Final Drive	Final Drive	Final Drive
Shaft	Shaft	Shaft
	CHASSIS SUSPENSION BRAKES	
Front Suspension	Front Suspension	Front Suspension
Double wishbone; 4.3 inch-travel	Double wishbone; 4.3 inch-travel	Double wishbone; 4.3 inch-travel
Rear Suspension	Rear Suspension	Rear Suspension
Pro Arm® single-side swingarm with Pro-Link® single	Pro Arm® single-side swingarm with Pro-Link® single	Pro Arm® single-side swingarm with Pro-Link® sin
shock; 4.1 inch-travel	shock; 4.1 inch-travel	shock; 4.1 inch-travel
Front Brake	Front Brake	Front Brake
Dual 320.0 mm discs	Dual 320.0 mm discs	Dual 320.0 mm discs
Rear Brake	Rear Brake	Rear Brake
Single 316.0 mm disc	Single 316.0 mm disc	Single 316.0 mm disc
Front Tire	Front Tire	Front Tire
130/70-18	130/70-18	130/70-18
Rear Tire	Rear Tire	Rear Tire
200/55-16	200/55-16	200/55-16
	DIMENSIONS	
Rake	Rake	Rake
30.0°	30.0°	30.5°
Trail	Trail	Trail
4.3 inches	4.3 inches	4.3 inches
Wheelbase	Wheelbase	Wheelbase
66.9 inches	66.9 inches	66.9 inches
Seat Height	Seat Height	Seat Height
29.3 inches	29.3 inches	29.3 inches

Curb Weight	Curb Weight	Curb Weight		
802 pounds (Includes all standard equipment, required	804 pounds (Includes all standard equipment, required	845 pounds (Includes all standard equipment, required		
fluids and a full tank of fuel)	fluids and a full tank of fuel)	fluids and a full tank of fuel)		
Fuel Capacity	Fuel Capacity	Fuel Capacity		
5.5 gallons	5.5 gallons	5.5 gallons		
FACTORY WARRANTY INFORMATION				
Duration	Duration	Duration		
Three-year transferable, unlimited-mileage limited	Three-year transferable, unlimited-mileage limited	Three-year transferable, unlimited-mileage limited		
warranty	warranty	warranty		
Optional Extended	Optional Extended	Optional Extended		
Up to five additional years extended coverage available	Up to five additional years extended coverage available	Up to five additional years extended coverage available		
with HondaCare® Protection Plan	with HondaCare® Protection Plan	with HondaCare® Protection Plan		