

Compare motorcycles



2025 XR650L

ENGINE

Engine Type 644cc air-cooled dry-sump single-cylinder four-stroke

Bore And Stroke

100.0 mm x 82.0 mm

Compression Ratio 8.3:1

Valve Train SOHC; four valves per cylinder RFVC[™]

Induction

42.5 mm diaphragm-type CV carburetor

DRIVETRAIN

Transmission

Five-speed manual

Final Drive

#520 O-ring-sealed chain; 15T/45T

CHASSIS SUSPENSION BRAKES
Front Suspension 43.0 mm Showa® cartridge fork; 11.6-inch travel
Rear Suspension Pro-Link® Showa® single-shock, 11.0-inch travel
Front Brake Single 256.0 mm disc with twin-piston caliper
Rear Brake Single 220.0 mm disc
Front Tire 3.00-21
Rear Tire 4.60-18
DIMENSIONS
Rake 27.0°
Trail 4.0 inches
Wheelbase 57.3 inches
Seat Height 37.0 inches

Curb Weight

346 pounds (Includes all standard equipment, required fluids and a full tank of fuel.)

Fuel Capacity

2.8 gallons

Ground Clearance

13.0 inches

FACTORY WARRANTY INFORMATION

Duration

Transferable, one year included, limited warranty

Optional Extended

Extended coverage available with a HondaCare® Protection Plan