

Image not found.

## 2020 PIONEER 1000-5 DELUXE SPECIFICATIONS\*

ENGINE	
Engine Type	999cc liquid-cooled twin-cylinder Unicam® four-stroke
Bore And Stroke	92.0mm x 75.15mm
Compression Ratio	10:1
Induction	Fuel Injection (PGM-FI), 44mm throttle body
Ignition	Full-transistorized with electronic advance
DRIVE TRAIN	
Transmission	Fully Automatic Dual Clutch Transmission (DCT) with six forward gears and Reverse. Four drive modes include 2WD, 4WD, Turf and Differential lock.
	Paddle Shifters with three shift modes (standard, sport, and manual)
Drivolino	Direct front and roar driveshafts

L	Driveline	Direc	t fron	t and	rear	drives	hatt	ts

CHASSIS SUSPENSION BRAI	KES
Front Suspension	Independent double-wishbone; 10.6 inches of travel
Rear Suspension	Independent double-wishbone; 10 inches of travel
Front Brake	Dual 210mm hydraulic discs
Rear Brake	Dual 210mm hydraulic discs
Front Tires	27 x 9-14
Rear Tires	27 x 11-14

	DIMENSIONS	
	Length	116.6 inches
	Width	63.0 inches
	Height	76.4 inches
	Wheelbase	80.2 inches
	Bed Capacity	1000 pounds for 49 states
	Bed Capacity	600 pounds for CA model
	Towing Capacity	2000 pounds
	Seat Height	33.3 inches
	Ground Clearance	12.4 inches
	Turning Radius	13.8 feet
	Curb Weight	1709 pounds - Includes all standard equipment, required fluids and full tank of fuel.
	Fuel Capacity	7.9 gallons, including 1.7-gallon reserve

OTHER	
Safety	Recommended for drivers 16 years of age and older.
Available Colors	Red, Honda Phantom Camo®, Reactor Blue
Model ID	SXS10M5D

FACTORY	WARRANTY	INFORMATION
---------	----------	-------------

One Year Included Transferable, limited warranty

Optional Extended Extended coverage available with a HondaCare Protection Plan®