



## 2023 CRF450R-S SPECIFICATIONS\*

| ENGINE                    |   |
|---------------------------|---|
| Engine Type               | 450cc liquid-cooled single-cylinder   |
| Bore And Stroke           | 96mm x 62.1mm   |
| Compression Ratio         | 13.5:1  |
| Valve Train               | Unicam SOHC; four valves per cylinder   |
| Induction                 | Programmed Fuel Injection (PGM-FI), 46mm downdraft throttle body  |
| DRIVE TRAIN               |   |
| Transmission              | Close-ratio five-speed  |
| Final Drive               | #520 Chain; 13T/49T   |
| CHASSIS SUSPENSION BRAKES |   |
| Front Suspension          | 49mm inverted Showa fork with rebound- and compression-damping adjustability; 12.0-inch travel                    |
| Rear Suspension           | Pro-Link Showa single shock with spring-preload, rebound- and compression-damping adjustability; 12.4-inch travel |
| Front Brake               | Single 260mm disc with twin-piston caliper  |
| Rear Brake                | Single 240mm disc   |
| Front Tire                | Dunlop MX33; 80/100-21  |
| Rear Tire                 | Dunlop MX33; 120/80-19  |
| DIMENSIONS                |   |
| Wheelbase                 | 58.4 inches   |
| Rake (Caster Angle)       | 27.4°   |
| Trail                     | 4.6 inches  |
| Seat Height               | 37.8 inches   |
| Ground Clearance          | 12.9 inches   |
| Fuel Capacity             | 1.7 gallons   |
| Curb Weight               | 247 pounds (Includes all standard equipment, required fluids and full tank of fuel)                               |
| OTHER                     |   |
| Available Colors          | Red   |
| Model ID                  | CRF450RS  |

\*All figures are preliminary and subject to change.

©2023 American Honda Motor Co., Inc. – Powersports Division