



2023 PIONEER 1000-6 DELUXE CREW SPECIFICATIONS*

ENGINE	
Engine Type	999cc longitudinally mounted liquid-cooled twin-cylinder four-stroke
Bore And Stroke	92.0mm x 75.2mm
Valve Train	Unicam® SOHC; four valves per cylinder
Compression Ratio	10:1
Induction	Programmed Fuel Injection (PGM-FI); 44mm throttle body
DRIVE TRAIN	
Transmission	Fully automatic Dual Clutch Transmission (DCT) with six forward gears, reverse, high/low subtransmission and paddle shifters; four drive modes (2WD, 4WD, Turf and Differential Lock); three shift modes (Standard, Sport, and Manual)
Driveline	Direct front and rear driveshafts
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 10.5-inch travel
Rear Suspension	Independent double-wishbone; 10.0-inch travel
Front Brake	Dual 210mm discs
Rear Brake	Dual 210mm discs
Front Tires	27 x 9-14
Rear Tires	27 x 11-14
DIMENSIONS	
Length	152.2 inches
Width	63.0 inches
Height	76.1 inches
Wheelbase	115.2 inches
Bed Capacity	1000 pounds (49 states); 600 pounds (CA model)
Towing Capacity	2500 pounds
Ground Clearance	12.6 inches
Turning Radius	18.7 feet
Curb Weight	1936 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	7.9 gallons, including 1.7-gallon reserve
OTHER	
Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Red, Olive, Honda Phantom Camo®
Model ID	SXS10M6DP
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.

©2023 American Honda Motor Co., Inc. – Powersports Division