



## 2023 PIONEER 700-4 SPECIFICATIONS\*

ENGINE	
Engine Type	675cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	102.0mm x 82.6mm
Compression Ratio	9.2:1
Induction	Fuel Injection (PGM-FI), 40mm throttle body
Valve Train	OHV; four valves per cylinder
DRIVE TRAIN	
Clutch	Automatic
Transmission	Automotive-style automatic transmission with hydraulic torque converter, three forward gears and Reverse. Three drive modes include 2WD, 4WD and 4WD with Differential lock. AT/MT modes with paddle shifting on the deluxe and Forest models.
Driveline	Direct front and rear driveshafts
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 7.9-inch travel
Rear Suspension	Independent double-wishbone; 9.1-inch travel
Front Brake	Dual 200mm hydraulic discs
Rear Brake	170mm hydraulic disc
Front Tires	25 x 8-12
Rear Tires	25 x 10-12
DIMENSIONS	
Length	114.8 inches
Width	59.9 inches
Height	77.9 inches
Wheelbase	76.8 inches
Bed Capacity	1000 pounds
Towing Capacity	1500 pounds
Ground Clearance	10.7 inches
Turning Radius	14.8 feet
Curb Weight	1433 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	8.1 gallons, including 1.5-gallon reserve
OTHER	
Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Olive, Black
Model ID	SXS700M4
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare Protection Plan®

\*All figures are preliminary and subject to change.

©2023 American Honda Motor Co., Inc. – Powersports Division