



2020 FOURTRAX RANCHER 4X4 AUTOMATIC DCT IRS SPECIFICATIONS*

ENGINE	
Engine Type	420cc liquid-cooled fuel-injected OHV wet-sump longitudinally mounted single-cylinder four-stroke
Bore And Stroke	86.5mm x 71.5mm
Induction	PGM-FI
Ignition	Full-transistorized type with electronic advance
Starter	Electric with optional auxiliary recoil
Compression Ratio	9.9:1
DRIVE TRAIN	
Clutch	Automatic
Transmission	Five-speed with reverse
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 7.28 inches of travel
Rear Suspension	Independent dual-arm; 8.46 inches of travel
Front Brake	190mm Dual hydraulic disc
Rear Brake	170mm Hydraulic disc
Front Tire	24 x 8-12
Rear Tire	24 x 10-11
DIMENSION	
Length	84.6 inches
Width	47.4 inches
Height	46.8 inches
Wheelbase	51.0 inches
Seat Height	34.9 inches
Ground Clearance	9.2 inches
Curb Weight	669 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Turning Radius	11.5 feet
OTHER	
Model ID	TRX420FA5
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Red, Olive
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owners manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan

*All figures are preliminary and subject to change.

©2019 American Honda Motor Co., Inc. – Powersports Division