



## 2020 FOURTRAX RANCHER SPECIFICATIONS\*

ENGINE	
Engine Type	420cc liquid-cooled fuel-injected OHV wet-sump longitudinally mounted single-cylinder four-stroke
Bore And Stroke	86.5mm x 71.5mm
Induction	PGM-FI
Ignition	Full-transistorized type with electronic system
Starter	Electric with optional auxiliary recoil
Compression Ratio	9.9:1
DRIVE TRAIN	
Clutch	Automatic
Transmission	Five-speed manual with reverse
Driveline	Direct rear driveshaft
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 6.69 inches of travel
Rear Suspension	Swingarm with single shock; 6.69 inches of travel
Front Brake	190mm Dual hydraulic disc
Rear Brake	160mm Sealed mechanical drum
Front Tire	24 x 8-12
Rear Tire	24 x 10-11
DIMENSIONS	
Length	82.8 inches
Width	47.4 inches
Height	46.2 inches
Wheelbase	50 inches
Seat Height	33.7 inches
Ground Clearance	7.2 inches
Curb Weight	580 pounds (includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Turning Radius	9.2 feet
OTHER	
Model ID	TRX420TM1
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Red, Olive
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owners manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan

\*All figures are preliminary and subject to change.