



2020 FOURTRAX RANCHER 4X4 SPECIFICATIONS*

ENGINE

Engine Type	420cc liquid-cooled fuel-injected OHV wet-sump longitudinally mounted single-cylinder four-stroke
Bore And Stroke	86.5mm x 71.5mm
Induction	PGM-FI
Ignition	Full-transistorized type with electronic advance
Starter	Electric with optional auxiliary recoil
Compression Ratio	9.9:1

DRIVE TRAIN

Clutch	Automatic
Transmission	Five-speed manual with reverse
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 6.69 inches of travel
Rear Suspension	Swingarm with single shock; 6.69 inches of travel
Front Brakes	190mm Dual hydraulic disc
Rear Brakes	160mm Sealed mechanical drum
Front Tires	24 x 8-12
Rear Tires	24 x 10-11

DIMENSIONS

Length	82.8 inches
Width	47.4 inches
Height	46.2 inches
Wheelbase	50.0 inches
Seat Height	33.7 inches
Ground Clearance	7.2 inches
Curb Weight	615 pounds (includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Turning Radius	9.2 feet
Front Rack Capacity	66 pounds
Rear Rack Capacity	133 pounds

OTHER

Model ID	TRX420FM1
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Red, Olive, Honda Phantom Camo®
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owners manual thoroughly.

FACTORY WARRANTY INFORMATION

*All figures are preliminary and subject to change.

©2021 American Honda Motor Co., Inc. – Powersports Division

One Year

Transferable limited warranty; extended coverage available with a Honda Protection Plan

*All figures are preliminary and subject to change.