



2020 FOURTRAX FOREMAN RUBICON 4X4 AUTOMATIC DCT EPS SPECIFICATIONS*

ENGINE	
Engine Type	518cc liquid-cooled OHV longitudinally mounted single-cylinder four-stroke engine
Bore And Stroke	92.0mm x 71.5mm
Induction	PGM-FI
Ignition	Full transistorized ignition
Starter	Electric with optional auxiliary recoil
DRIVE TRAIN	
Clutch	Automatic
Transmission	Five-speed automatic dual-clutch transmission with reverse and Low/Drive sub-transmission
Driveline	Direct front and rear driveshafts with TraxLok® and locking front differential
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 7.28 inches of travel
Rear Suspension	Independent dual-arm; 8.46 inches of travel
Front Brakes	190mm hydraulic discs
Rear Brakes	170mm hydraulic disc
Front Tires	25 x 8-12
Rear Tires	25 x 10-12
DIMENSIONS	
Length	84.5 inches
Width	47.4 inches
Height	48.6 inches
Wheelbase	50.9 inches
Seat Height	35.8 inches
Ground Clearance	9.4 inches
Curb Weight	729 pounds (includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Towing Capacity	1322 pounds
Front Rack Capacity	99 pounds
Rear Rack Capacity	187 pounds
OTHER	
Model ID	TRX520FA6
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Red, Olive
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan.

*All figures are preliminary and subject to change.

©2020 American Honda Motor Co., Inc. – Powersports Division