



2023 FOURTRAX FOREMAN RUBICON 4X4 AUTOMATIC DCT EPS SPECIFICATIONS*

ENGINE

Engine Type	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke
Bore And Stroke	96.0mm x 71.5mm
Compression Ratio	9.5:1
Valve Train	OHV; two valves per cylinder
Induction	Programmed Fuel Injection (PGM-FI); 36mm throttle body
Starter	Electric with optional auxiliary recoil

DRIVE TRAIN

Clutch	Automatic
Transmission	Five-speed automatic dual-clutch transmission with reverse and Low/Drive sub-transmission
Driveline	Direct front and rear driveshafts with TraxLok® and locking front differential

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 7.3-inch travel
Rear Suspension	Independent dual-arm; 8.5-inch travel
Front Brakes	Dual 190mm discs
Rear Brakes	Dual 170mm discs
Front Tires	25 x 8-12
Rear Tires	25 x 10-12

DIMENSIONS

Length	86.0 inches
Width	47.4 inches
Height	48.7 inches
Wheelbase	50.9 inches
Seat Height	36.3 inches
Ground Clearance	9.7 inches
Curb Weight	725 pounds (includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Towing Capacity	1322 pounds
Front Rack Capacity	99 pounds
Rear Rack Capacity	187 pounds

OTHER

Model ID	TRX520FA6
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Red, Black Forest Green
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
-------------------	--------------------------------

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division

Optional Extended

Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.