



2023 FOURTRAX RINCON SPECIFICATIONS*

ENGINE

Engine Type	675cc liquid-cooled OHV semi-dry-sump longitudinally mounted single-cylinder four-stroke
Bore And Stroke	102mm x 82.6mm
Ignition	9.2:1
Valve Train	OHC; four valves per cylinder
Induction	Electronic fuel injection (PGM-FI), 40mm throttle body
Starter	Electric with auxiliary recoil

DRIVE TRAIN

Transmission	Five-speed automatic DCT with high/low range
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 6.9 inches of travel
Rear Suspension	Independent double-wishbone; 8.0 inches of travel
Front Brakes	Dual 180mm disc
Rear Brakes	170mm disc
Front Tires	25 x 8-12
Rear Tires	25 x 10-12

DIMENSIONS

Length	83.3 inches
Width	46.7 inches
Height	47.5 inches
Wheelbase	50.6 inches
Seat Height	34.5 inches
Ground Clearance	9.1 inches
Curb Weight	658 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	4.4 gallons, including 1.2-gallon reserve
Turning Radius	10.8 feet
Towing Capacity	848 pounds
Front Rack Capacity	66 pounds
Rear Rack Capacity	132 pounds

OTHER

Model ID	TRX680FA
Emissions	Meets current EPA off-road emissions standards. Not available in California or for California use.
Available Colors	Red
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
-------------------	--------------------------------

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division

Optional Extended

Extended coverage available with a HondaCare Protection Plan®

*All figures are preliminary and subject to change.