



2024 FOURTRAX FOREMAN 4X4 ES EPS SPECIFICATIONS*

ENGINE

Engine Type	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke
Bore And Stroke	96.0mm x 71.5mm
Compression Ratio	9.5:1
Valve Train	OHV; two valves per cylinder
Induction	Programmed Fuel Injection (PGM-FI); 36mm throttle body
Starter	Electric with optional auxiliary recoil

DRIVE TRAIN

Clutch	Automatic
Transmission	Five-speed with reverse
Driveline	Direct front and rear driveshafts with TraxLok® and front differential lock

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 7.3-inch travel
Rear Suspension	Swingarm with single shock; 7.3-inch travel
Front Brakes	Dual 190mm discs
Rear Brakes	160mm sealed mechanical drum
Front Tires	25 x 8-12
Rear Tires	25 x 10-12

DIMENSIONS

Length	82.9 inches
Width	47.4 inches
Height	47.8 inches
Wheelbase	50.0 inches
Seat Height	34.5 inches
Ground Clearance	7.5 inches
Curb Weight	653 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Turning Radius	10.5 feet
Towing Capacity	848 pounds
Front Rack Capacity	88 pounds
Rear Rack Capacity	176 pounds

OTHER

Model ID	TRX520FE2
Emissions	Meets current EPA CARB (California) off-road emissions standards.
Available Colors	Avenger Red, Krypton Green, Sandstone Beige, Honda Phantom Camo®
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
-------------------	--------------------------------

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division

Optional Extended

Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.