



2024 FOURTRAX RUBICON 4X4 AUTOMATIC SPECIFICATIONS*

ENGINE

Engine Type	675cc longitudinally mounted liquid-cooled single-cylinder four-stroke
Bore And Stroke	102.0mm x 82.6mm
Ignition	9.2:1
Valve Train	OHC; four valves per cylinder
Induction	Electronic fuel injection (PGM-FI); 40mm throttle body
Starter	Electric with auxiliary recoil

DRIVE TRAIN

Transmission	Automatic with hydraulic torque converter; three forward gears, reverse, and electronic controls
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 6.9-inch travel
Rear Suspension	Independent dual-arm; 8.0-inch travel
Front Brakes	Dual 180mm discs
Rear Brakes	170mm disc
Front Tires	26 x 8-12
Rear Tires	26 x 10-12

DIMENSIONS

Length	86.5 inches
Width	47.5 inches
Height	48.0 inches
Wheelbase	50.6 inches
Seat Height	36.3 inches
Ground Clearance	9.5 inches
Curb Weight	701 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	4.4 gallons, including 1.2-gallon reserve
Turning Radius	10.8 feet
Towing Capacity	848 pounds
Front Rack Capacity	99 pounds
Rear Rack Capacity	187 pounds

OTHER

Available Colors	Avenger Red; Matte Silver Metallic
Model ID	TRX700FA
Emissions	Meets current EPA off-road emissions standards. Not available in California or for California use.
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
-------------------	--------------------------------

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division

Optional Extended

Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.