



2025 FOURTRAX FOREMAN RUBICON 4X4 EPS SPECIFICATIONS*

ENGINE

Engine Type	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke
Bore And Stroke	96.0mm x 71.5mm
Compression Ratio	9.5:1
Valve Train	OHV; two valves per cylinder
Induction	Programmed Fuel Injection (PGM-FI); 36mm throttle body
Starter	Electric with optional auxiliary recoil

DRIVE TRAIN

Clutch	Automatic
Transmission	Five-speed manual with reverse
Driveline	Direct front and rear driveshafts with TraxLok® and locking front differential

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 7.3-inch travel
Rear Suspension	Independent dual-arm; 8.5-inch travel
Front Brakes	Dual 190mm discs
Rear Brakes	Dual 170mm discs
Front Tires	25 x 8-12
Rear Tires	25 x 10-12

DIMENSIONS

Length	86.0 inches
Width	47.4 inches
Height	48.7 inches
Wheelbase	50.9 inches
Seat Height	36.3 inches
Ground Clearance	9.7 inches
Turning Radius	11.5 feet
Curb Weight	697 pounds (includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Towing Capacity	1322 pounds
Front Rack Capacity	99 pounds
Rear Rack Capacity	187 pounds

OTHER

Model ID	TRX520FM6
Emissions	Meets current EPA and CARB (California) off-road emissions standards.
Available Colors	Hero Red, Black Forest Green, Matte Gray Metallic
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division

One Year Included
Optional Extended

Transferable, limited warranty
Extended coverage available with a HondaCare® Protection Plan