



2026 FOURTRAX RECON ES SPECIFICATIONS*

ENGINE

Engine Type	229cc air-cooled longitudinally mounted single-cylinder four-stroke
Bore And Stroke	68.5mm x 62.2mm
Compression Ratio	9.2:1
Valve Train	OHV; two valves per cylinder
Induction	22mm piston-valve carburetor
Starter	Electric with optional auxiliary recoil

DRIVETRAIN

Transmission	Five-speed ATV-style semi-automatic with reverse
Driveline	Direct rear driveshaft

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 5.1-inch travel
Rear Suspension	Swingarm with single shock; 4.9-inch travel
Front Brakes	Dual 130mm drums
Rear Brake	140mm drum
Front Tires	22 x 7-11
Rear Tires	22 x 10-9

DIMENSIONS

Length	75.0 inches
Width	40.7 inches
Height	42.1 inches
Wheelbase	44.5 inches
Seat Height	31.2 inches
Ground Clearance	6.0 inches
Turning Radius	8.5 feet
Curb Weight	443 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	2.4 gallons
Front Rack Capacity	33.0 pounds
Rear Rack Capacity	66.0 pounds
Towing Capacity	500.0 pounds

OTHER

Available Colors	Hero Red, Black Forest Green
Model ID	TRX250TE
Emissions	Meets current EPA off-road emissions standards. Not available in California or for California use.
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

Duration	Transferable, one year included, limited warranty
----------	---------------------------------------------------

*All figures are preliminary and subject to change.

Optional Extended

Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.