2026 FOURTRAX RUBICON 700 4X4 AUTOMATIC SPECIFICATIONS*

ENGINE	
Engine Type	675cc liquid-cooled longitudinally mounted single-cylinder four-stroke
Bore And Stroke	102.0mm x 82.6mm
Compression Ratio	9.2:1
Valve Train	OHC; four valves per cylinder
Induction	Programmed Fuel Injection system (PGM-FI); 40mm throttle body
Starter	Electric with optional auxiliary recoil

DRIVETRAIN	
Transmission	Automatic with hydraulic torque converter; three forward gears, reverse, and electronic controls
Driveline	Direct front and rear driveshafts with torque-sensitive locking front differential

CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 6.9-inch travel
Rear Suspension	Independent dual-arm; 8.0-inch travel
Steering	Manual
Front Brakes	Dual 180mm discs
Rear Brake	170mm disc
Front Tires	26 x 8-12
Rear Tires	26 x 10-12

DIMENSIONS	
Length	86.5 inches
Width	47.5 inches
Height	48.0 inches
Wheelbase	50.6 inches
Seat Height	34.8 inches
Ground Clearance	9.5 inches
Curb Weight	701 pounds (includes all standard equipment, required fluids and a full tank of fuel)
Fuel Capacity	4.4 gallons
Turning Radius	10.8 feet
Towing Capacity	848 pounds
Front Rack Capacity	99.0 pounds
Rear Rack Capacity	187.0 pounds

OTHER	
Available Colors	Hero Red, Matte Silver
Model ID	TRX700FA
Emissions	Meets current EPA off-road emissions standards. Not available in California or for California use.
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

*All figures are preliminary and subject to change.

©2026 American Honda Motor Co., Inc. – Powersports Division

Duration	Transferable, one year included, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2026 American Honda Motor Co., Inc. – Powersports Division