



2024 TRX250X SPECIFICATIONS*

ENGINE

Engine Type	229cc air-cooled OHV longitudinally mounted single-cylinder four-stroke
Bore And Stroke	68.5mm x 62.2mm
Compression Ratio	9.2:1
Valve Train	OHV; two valves per cylinder
Induction	22mm piston-valve carburetor
Starter	Electric

DRIVE TRAIN

Transmission	Five-speed with reverse; Honda SportClutch™
Driveline	Direct rear driveshaft

CHASSIS SUSPENSION BRAKES

Front Suspension	Independent double-wishbone; 5.9-inch travel
Rear Suspension	Swingarm with single shock; 5.7-inch travel
Front Brakes	Dual 174mm discs
Rear Brake	Sealed 140mm drum
Front Tires	22 x 7-10
Rear Tires	22 x 10-9

DIMENSIONS

Length	68.5 inches
Width	41.8 inches
Height	42.6 inches
Wheelbase	44.3 inches
Seat Height	31.4 inches
Ground Clearance	5.7 inches
Curb Weight	385 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	2.5 gallons, including 0.7-gallon reserve
Turning Radius	9.2 feet

OTHER

Model ID	TRX250X
Available Colors	Red, Solstice Orange
Emissions	Meets current EPA off-road emissions standards. Not available in California or for California use.
Important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.

FACTORY WARRANTY INFORMATION

One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.